

SECTION B-B

[illegible]

Technical drawing of the handle assembly. The drawing shows a side view of the handle with the following dimensions and labels:

- Top left dimension: 31.75 mm [1.250 in]
- Bottom left dimension: R3.18 mm [R0.125 in]
- Top center label: HANDLE MOUNTING HOLES
- Bottom center dimension: 466.01 mm [18.347 in]
- Right side dimension: 10.72 mm [0.422 in]

This diagram illustrates the exploded view of the 1000 Series 12U Rack Mountable Power Supply Unit (PSU). It shows the PSU, the mounting brackets, and the screws used for installation. The PSU is shown in the center, with the mounting brackets positioned above and below it. The screws are shown in their respective positions, indicating how they are used to secure the PSU into the rack.

Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory - mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.

RM1U1928VBK	
Extruded Aluminum Frame - Type 6063	
2 Panels - .064" Aluminum (5052-H32) Powder Coat	
2 Mounting Brackets - .125" Aluminum	
24 Screws - Flat Head 4-40 x 3/8"	
8 Screws - Counter Sunk Head 6-32 x 3/8"	
4 Screws - Counter Sunk Head 10-32 x 3/8"	
24 Nuts - #4 Speed Nuts	
Four Self Adhesive Rubber Feet - 1421T3	
ACCESSORIES	
PULL HANDLES	1427B2BK
REAR BRACKET KIT	RM1U18BRKT



HAMMOND
MANUFACTURING™

RM1U1928VBK

www.hammondmfg.com