

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 11019

SKU 11019

規格					RADIL TYPE ⊥ D ⊥ ⊥ P ⊥ ⊥ 0 ⊥ ⊥ L ±1 ⊥ ⊥ 0 ±1 ⊥		AXIAL TYPE ⊥ D ⊥ ⊥ L ±1 ⊥ ⊥ D ±1 ⊥ ⊥ D ⊥	
SPEC 220UF 50 V								
GSA (ROHS)								
D	L	P	L	d				
10	17		35	0.6				
使用溫度範圍					OPERATION		TEMPERATURE RANGE -40℃--+85℃	

Specification:

Operation temperature range $-40\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$

Capacitance tolerance: 220UF at 120Hz , -20% $+20\%$

Leajage current: 110 uA after 1 minute applied rated voltage

Tan δ (dissipation factor) at 120Hz, 10 %

Surge voltage: 63 volt

Ripple current: 410 mA RMS at 120 Hz, 85°C

Impedance: Ω MAX at 120 Hz, 20°C

Impedance ration:

Laod life: 2000 Hrs at 85°C

Shelf life: 2000 Hrs at 85°C

CCA After Hrs application of rated voltage at 85°C , capacitor must meet the characteristics requiremnts listed below:

Capacitance change within $\pm 25\%$ of initial value

Tan δ : 200% or less than initial value

Leakage current: Less than initial value

TEST REPORT

[illegible]