






MATERIAL LIST :

NO	Material	
1	BOBBIN	NYLON
2	SILICON	H 50
3	WIRE	2UEW 130°C
4	TAPE	
5	PAPER	0.25 mm
6	PVC	1015*20AGW
7	PVC	1015*20AGW
8	L	
9		

GOLDSUN ELECTRONICS CO., LTD.


JAMECO NO.	149957	GOLDSUN NO.	EI-66x25-R
Description	POWER TRANS. I/P:115/230VAC O/P: 18VCT 2A, WIRE LEADS		Rev. 1
UNIT:	SCALE:	SHEET 1 OF 1	CAS No: ERN No:

一、Size :



GOLDSUN ELECTRONICS CO., LTD.

JAMECO NO. 149957		GOLDSUN NO. EI-66x25-R	
Description POWER TRANS. I/P:115/230VAC O/P: 18VCT 2A, WIRE LEADS			Rev. 1
UNIT: mm	SCALE:	SHEET 1 OF 1	CAS No: ERN No:



1. TYPE: Single Phase Power Transformer
2. Output capacity: 35 VA
3. Primary Voltage: 115V 230V
4. Primary Voltage: P1 : 9V P2 : 18V
5. Secondary current: P1 : 2A P2 : 2A
6. Frequency : 50/60Hz
7. Time frame: continuous
8. Insulation resistance: DC500V 100MΩabove
9. Insulation endurance: AC1500V 1min 50Hz P-S
10. Temperature: Below 70deg
11. Voltage mobility rate: below 10%
12. Voltage deviation: within ±5%
13. RoHS

GOLDSUN ELECTRONICS CO., LTD.			
JAMECO NO. 149957		GOLDSUN NO. EI-66x25-R	
Description POWER TRANS. I/P:115/230VAC O/P: 18VCT 2A, WIRE LEADS			Rev. 1
UNIT: mm	SCALE:	SHEET 1 OF 1	CAS No: ERN No: