





Date	Rev.	Description



10.	Washer	0.3T Steel	1	Nickel Plated
9.	Nut	2.1T Brass	1	Nickel Plated
8.	Insulator	Bakelite	1	Red Color
7.	Insulator	Bakelite	1	Red Color
6.	Pin(2.5φ)	Copper	1	Nickel Plated
5.	Break Terminal	0.3T Phosphor Bronze	1	Silver Plated
4.	Sleeve Spring	0.3T Brass	1	Silver Plated
3.	Pin Terminal	0.3T Brass	1	Silver Plated
2.	Housing	PBT	1	Black Color
1.	Bushing	Brass	1	Nickel Plated
NO.	Description	Material	Q'TY	Finish

SPECIFICATIONS:
Contact Resistance : 30mΩ max
Insulation Resistance : 100MΩ min. at DC 500V
Dielectric Withstanding Voltage: AC 500V for one minute
Remark: ▲: The Most Important Dimension

RoHS
Compliant

DCC. NO.
A4 DRAWING NO.

MATERIAL
DRAWN: Colin Hang
VERIFY PEOPLE: Penny

GOLDSUN ELECTRONICS CO., LTD.
JAMECO NO. 151563
GOLDSUN NO. SCD554DCSA03B00G
Description POWER JACK, PC MOUNT
CENTER PIN 2.5mm
UNIT: mm SCALE: SHEET 1 OF 1
CAS No: ERN No: