

JACKCON CERAMIC DISC CAPACITORS

DATE: 2022.11.02


CUSTOMER: JAMECO ELECTRONICS LTD

DESCRIPTION: CERAMIC CAPACITOR

SPEC.: CC10PF($\pm 10\%$)50V SL P : 5mm

P/N: CC100K1HSD5LS

CUST. P/N: 15333

BUYER'S APPROVAL STAMP	APPROVED BY:	TESTED BY:
		
	2022.11.02	2022.11.02

HONJU TAIWAN CO., LTD

JACKCON CAPACITOR ELECTRONICS CO., LTD.

SUPPLIER : JACKCON CAPACITOR ELECTRONICS CO., LTD.
5F, NO.88, SHING DE ROAD, SAN CHUNG CITY,
TAIPEI COUNTY, TAIWAN

TEL : 886-2-2278-2210 886-2-2278-2212

FAX : 886-2-2278-2656 886-2-2278-2640

www.jackcon.com.tw

qc@jackcon.com.tw

CERAMIC DISC CAPACITORS

陶 瓷 電 容 器

SPECIFICATION FOR APPROVAL			
承 認 規 格			
CUSTOMER 客 戶		DATE 日 期	2022/11/02
USER PART NO. 客戶零件代號		description 品 名	陶瓷電容器
USED SPEC. 適用規格	V		
		D: 5 MAX T: 3 MAX F: 5.0 ± 0.8 L: 25 ± 2 MIN d: 0.48 ± 0.05 B: 3 MAX COLOR CODE: 顏色 ☒ 土黃色 ☐ EPOXY (藍色)	
SPECIFICATIONS 規 格			
RATED CAP. 公稱靜電容量	10 PF	LIFE TEST (ENDURANCE) 高 溫 負 荷	
CAP. TOL. 靜電容量容許差	$\pm 10\%$	CAP. CHANG % 靜 電 容 量 變 化	
TEMP. CHARACT 溫 度 特 性	SL	Q $\tan \delta$	MIN % MAX
INITIAL Q 初期 Q	600 MIN	INSULATION RESISTANCE 絕 緣 電 阻	MΩ MIN
RATED VOLTAGE 額 定 電 壓	DC 50V	HUMIDITY LIFE TEST 耐 濕 負 荷	
VLOTAGE PROOF 耐 電 壓		CAP. CHANG % 靜電容量變化	±
BETWEEN TERMINALS 端 子 間	☐ AC V FOR 60 SEC ☒ DC 150V FOR 1~5 SEC	Q $\tan \delta$	MIN % MAX
BETWEEN 端子外裝間 TERNHXABS&COATING	DC V	本公司承認欄	
INITIAL 初期絕緣電阻 INSULATION RESISTANCE	10,000 MΩ MIN		
CUSTOMER'S SIGNATURE 貴 公 司 承 認 欄		Approval 核 決	Chief 審 核
		Inspector 檢 驗	
		副總經理 2022/11/02 洪仁良	品保經理 2022/11/02 曾立文
		QC 2022/11/02 TQC02	