





Part No.	Order No.	Pcs/Pkt.
UKK80A	100401001	10
I=80 A IEC 60947-7-1		
I=85 Amp UL/CSA		
Icw KA rms Is:3	Ipk KA:22	
Ui:690V IEC	Vin:600V UL	
Installation hole distance:54mm		
Modularity: single stranded wire, can be expanded by jumper wire, and doubled neutral wire		




公制	 mm ²	 mm ²	Γ (N.m)
	6-16	x1	 2.5
	2.5-16	x4	 1.8
	2.5-16	x2	 2.5
美规	AWG		力矩
	16-4	x1	 17.5
	16-8	x4	 10.6
	16-4	x2	 17.5

Part No.	Order No.	Pcs/Pkt.
UKK125A	100401002	10
I=125 A IEC 60947-7-1		
I=125 Amp UL/CSA		
Icw KA rms Is:4.2	Ipk KA:30	
Ui:690V IEC	Vin:600V UL	
Installation hole distance:64mm		
Modularity: single stranded wire, can be expanded by jumper wire, and doubled neutral wire		



公制	 mm²	 mm²	Γ (N.m)
	10-35	x1	 4.0
	6-16	x1	 2.5
	2.5-16	x6	 2.5
美规	AWG		力矩
	8-1/0	x1	 35
	14-4	x1	 17.5
	14-4	x6	 17.5

Part No.	Order No.	Pcs/Pkt.
UKK160A	100401003	10
I=160 A IEC 60947-7-1		
I=200 Amp UL/CSA		
Icw KA rms Is:11.8	Ipk KA:30	
Ui:690V IEC	Vin:600V UL	
Installation hole distance:64mm		
Modularity: single stranded wire, can be expanded by jumper wire, and doubled neutral wire		



公制	 mm²	 mm²	Γ (N.m)
	10-70	x1 	2.5
	6-16**	x1 	1.8
	2.5-16	x6 	2.5
美规	AWG	力矩	
	8-3/0	x1 	17.5
	14-4	x1 	10.6
	14-4	x6 	17.5