

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 2082450


SERIES 76

SPST Rocker



FEATURES


- Raised and Recessed, Rocker and PIANO-DIP® Styles
- Sealed Base Standard
- Spring and Ball Contact
- Top Tape Seal Option



DIMENSIONS In inches (and millimeters)

Rocker and Recessed Rocker	Side Actuated PIANO-DIP®	PIANO-DIP®
<p>LENGTH $\pm .010$ (± 0.25) SEE ORDER INFO.</p> <p>1 2 3 4 5 6 7 OPEN OPEN</p> <p>.380 $\pm .010$ (9.65 ± 0.25)</p> <p>.090 $\pm .005$ (2.29 ± 0.13)</p> <p>.020 $\pm .002$ (0.51 ± 0.05)</p> <p>.100 $\pm .005$ (2.5 ± 0.13)</p> <p>See also end view.</p>	<p>LENGTH $\pm .010$ (± 0.25) SEE ORDER INFO.</p> <p>OPEN</p> <p>.380 $\pm .010$ (9.65 ± 0.25)</p> <p>.090 $\pm .005$ (2.29 ± 0.13)</p> <p>.020 $\pm .002$ (0.51 ± 0.05)</p> <p>.100 $\pm .005$ (2.5 ± 0.13)</p> <p>See also end view.</p>	<p>End Views</p> <p>B = $.156 \pm .010$ (3.96 ± 0.25) TYPICAL</p> <p>.281 $\pm .010$ (7.14 ± 0.25)</p> <p>.020 $\pm .005$ (0.51 ± 0.13)</p> <p>.012 $\pm .001$ (0.30 ± 0.03)</p> <p>.300 $\pm .030$ (7.62 ± 0.76)</p> <p>Rocker</p> <p>A = $.272 \pm .010$ (6.91 ± 0.25)</p> <p>.295 $\pm .000$ -.020 (7.49 ± 0.51)</p> <p>.156 $\pm .010$ (3.96 ± 0.25) TYP.</p> <p>.020 $\pm .005$ -.000</p> <p>.012 $\pm .001$ (0.30 ± 0.03)</p> <p>.300 $\pm .030$ (7.62 ± 0.76)</p> <p>For recessed rockers, delete .295 dimension.</p>

CIRCUITRY



ORDERING INFORMATION

Series	No. of Pos.	Length (Inches)	Length (Metric)	No./Tube
Switch Style: SB = Raised Rocker	2	0.280"	7.1 mm	35
RSB = Recessed Rocker	3	0.380"	9.7 mm	27
PSB = Piano-DIP (Up is Off)	4	0.480"	12.2 mm	21
PRB = Piano-DIP (Up is On)	5	0.580"	14.7 mm	18
	6	0.680"	17.3 mm	15
	7	0.780"	19.8 mm	13
	8	0.880"	22.4 mm	12
	9	0.980"	24.9 mm	10
	10	1.080"	27.4 mm	9
	12	1.280"	32.5 mm	8

*A top tape seal is required for switches that are machine soldered or heavily cleaned after hand soldering. To order top seal versions, add "S" to the Grayhill part number.

Available from your local Grayhill Distributor.
For prices and discounts, contact a local Sales Office, an authorized local Distributor or Grayhill.

SPECIFICATIONS: Standard Styles

Ratings	76	78	90B
Mechanical Life: Operations per switch position	2,000	2,000	2,000
Make-and-break Current Rating: Operations per switch position at these resistive loads			
1 mA, 5 Vdc; 50 mA, 30 Vdc; or 150 mA, 30 Vdc:	2,000	2,000	—
10 mA, 30 Vdc; or 10 mA, 50 mVdc:	—	—	2,000
10 mA, 50 mVdc; or 25 mA, 24 Vdc; or 100 mA, 6 Vdc:	—	—	2,000
Contact Resistance: Initially:	$\leq 30 \text{ m}\Omega$	$\leq 30 \text{ m}\Omega$	$\leq 20 \text{ m}\Omega$
After life, at 10 mA, 50 mVdc, open circuit:	$\leq 100 \text{ m}\Omega$	$\leq 100 \text{ m}\Omega$	$\leq 100 \text{ m}\Omega$
Insulation Resistance:			
Minimum, at 100 Vdc between adjacent closed contacts and also across open switch contacts			
Initially (Mohms):	5,000	5,000	5,000
After life (Mohms):	1,000	1,000	1,000
Dielectric Strength: Minimum voltage (AC, RMS) measured between adjacent closed contacts and also across open switch contacts.			
Initially:	750 V	750 V	500 V
After life:	500 V	500 V	500 V
Current Carry Rating: Maximum rise of 20°C	5 A	4 A	3 A
Switch Capacitance: At 1 megahertz	2 pF	2 pF	2 pF
Operating Temperature Range:	-40°C to + 85°C	-40°C to + 85°C	-40°C to + 85°C
Storage Temperature Range:	-55°C to + 85°C	-55°C to + 85°C	-55°C to + 85°C

Mechanical Ratings

Vibration Resistance: Per Method 204, Test Condition B, 1 mS opening (10 mS allowed)

Mechanical Shock: Per Method 213, Test Condition A. 1 mS opening (10 mS allowed)

Thermal Shock Resistance: Per specification; no failures; passes contact resistance.

Terminal Strength: Per specification

Thermal Aging: 1,000 hours at 85°C; no failures.

Environmental Ratings

Meets all requirements of MIL-S-83504. Where Grayhill performance is superior, the MIL spec is listed in parentheses.

Moisture Resistance: Per MIL-STD-202, Method 106.

Soldering Information

Series 90 MIDIP and Series 76 recessed rocker (76RSB style) sealed switches have been tested to EIA Standard RS-448-2. Similar performance can be expected from other sealed Series 76 and 78 DIP switches.

Solderability: Per MIL-STD-202, Method 208

Resistance to Soldering Heat: 76RSB: Passes EIA Standard using two, four, and six second soldering time. 90: Per MIL-S-83504, six second test.

Fluxing: Per EIA RS-448-2 with flux touching switch body.

Cleaning: 76, 78 and 90 series tape sealed products: Passes immersion test using water/detergent. Acceptable solutions include 1-1-1 trichlorethane, freon, (TF, TE, or TMS), isopropyl alcohol, detergent (140°F maximum). Terpene acceptable for Series 90 only. Solutions which are not recommended include acetone, methylene chloride, freon TMC.

Materials and Finishes

Shorting Member (Ball): Brass, gold-plated over nickel barrier.

Base Contacts: Copper alloy, gold-plated over nickel barrier.

Terminals: Copper alloy, matte tin plated over nickel barrier.

Non-Conductive Parts: Thermoplastic (UL94V-O)

Potting Material: Epoxy, 76,78 only.

Protective Cover: 76,78, only-Polycarbonate.

Tape Seal:


76, 78: Polyester film

90: Polyimide film

Tape Seal Integrity: Passes gross leak test using 125°C flourinert for 20 seconds minimum. Reference MIL-STD-202, Method 112.

Reflow Soldering Profile:

(260°C Peak Temperature)



WAVE SOLDERING: 260°C maximum solder temperature for 5 seconds max.