

插入型絕緣/金屬軸式編碼規則

RV 09 A X F - 40 E1 - 20 F X - B 5K - X X XXX
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

1. Product Line

RV Rotary Potentiometer

2. Model

3. Structure Difference

4. Derivatives

5. RoHS Version

F indicates RoHS Compliance

6. Type of Terminal

Code	Type of Terminal
10	Solder lug
20	PC board (horizontal)
30	PC board (vertical);front
40	PC board (vertical);back

7. Type of Bushing

8. Shaft Length

9. Type of Shaft

10. Axis Angle of F-type Shaft

11. Pattern of Resistance Curve

12. Resistance Value

13. Materials & Methods for Manufacturing Shaft & Bushing

14. Number of Click

Code	Specification
0	None
C	Center Click
D	11 Positions click
E	21 Positions click
F	41 Positions click

15. Serial No.

訂單指定事項：

開立訂單時，用途請依下表記載予以指定製品之規格詳細記載並確認之。

項目：

1. 型號。
2. 公稱阻值及線性要求。
3. 軸型及長度。
4. 端子型式。
5. 段點的有無。
6. 中間抽頭的有無。
7. 音量用或其他。
8. 手焊錫或錫爐焊錫。

ORDERING INSTRUCTIONS

WHEN PLACING YOUR ORDER, PLEASE SPECIFY THE FOLLOWING ITEMS ACCORDING TO YOUR APPLICATION NEEDS. FOR MORE INFORMATION ABOUT OUR PRODUCTS, PLEASE REFER TO THE SPECIFICATION GIVEN ON THE FOLLOWING PAGES.

ITEMS：

1. MODEL.
2. NORMAL RESISTANCE VALUE AND TAPER.
3. SHAFT STYLE AND LENGTH.
4. TERMINAL STYLE.
5. WITH CLICK OR WITHOUT CLICK, CLICK POSITION
6. WITH TAP OR WITHOUT TAP, TAP POSITION.
7. FOR VOLUME CONTROL OR OTHER USE.
8. MANUAL SOLDERING OR DIP SOLDERING.

[illegible]

Model	Outline Drawing	Features / Individual Specification																																
RV24A01F-10(S.P.S.T.) RV24A02F-10(S.P.D.T.)		300° rotation, mono unit with Rotary SW S.P.S.T. 125VAC 1A S.P.D.T. 125V AC 1A																																
RV24A03F-40D2 (Plastic Shaft & Bushing)		300° rotation, mono unit with Rotary SW S.P.S.T. 125V AC 1A PCB Mounting Hole Detail																																
TERMINAL LAYOUT RV24A01F, RV24A02F, RV24A03F																																		
SPECIFICATION (RV24A01F, RV24A02F, RV24A03F)																																		
<table><tr><td colspan="2">MECHANICAL</td><td colspan="2">ELECTRICAL</td></tr><tr><td>TOTAL ROTATION ANGLE</td><td>300°±5°</td><td>linear taper (B)</td><td>other tapers</td></tr><tr><td>ROTATION TORQUE</td><td>20~200 gf.cm</td><td>0.5W</td><td>0.25W</td></tr><tr><td>SHAFT STOP STRENGTH</td><td>6kgf.cm/Min.</td><td>500V</td><td>250V</td></tr><tr><td>SWITCH WORKING ANGLE</td><td>50°±10°</td><td>INSULATION RESISTANCE</td><td>more than 100MΩ at 500V DC</td></tr><tr><td>SWITCH WORKING TORQUE</td><td>800gf.cm Max/</td><td>DIELECTRIC STRENGTH</td><td>500V AC, 1 minute</td></tr><tr><td>SWITCH CIRCUIT</td><td>S.P.S.T., S.P.D.T.</td><td>SWITCH CONTACT RESISTANCE</td><td>less than 30mΩ</td></tr><tr><td></td><td></td><td>SWITCH RATING</td><td>125V AC, 1A</td></tr></table>			MECHANICAL		ELECTRICAL		TOTAL ROTATION ANGLE	300°±5°	linear taper (B)	other tapers	ROTATION TORQUE	20~200 gf.cm	0.5W	0.25W	SHAFT STOP STRENGTH	6kgf.cm/Min.	500V	250V	SWITCH WORKING ANGLE	50°±10°	INSULATION RESISTANCE	more than 100MΩ at 500V DC	SWITCH WORKING TORQUE	800gf.cm Max/	DIELECTRIC STRENGTH	500V AC, 1 minute	SWITCH CIRCUIT	S.P.S.T., S.P.D.T.	SWITCH CONTACT RESISTANCE	less than 30mΩ			SWITCH RATING	125V AC, 1A
MECHANICAL		ELECTRICAL																																
TOTAL ROTATION ANGLE	300°±5°	linear taper (B)	other tapers																															
ROTATION TORQUE	20~200 gf.cm	0.5W	0.25W																															
SHAFT STOP STRENGTH	6kgf.cm/Min.	500V	250V																															
SWITCH WORKING ANGLE	50°±10°	INSULATION RESISTANCE	more than 100MΩ at 500V DC																															
SWITCH WORKING TORQUE	800gf.cm Max/	DIELECTRIC STRENGTH	500V AC, 1 minute																															
SWITCH CIRCUIT	S.P.S.T., S.P.D.T.	SWITCH CONTACT RESISTANCE	less than 30mΩ																															
		SWITCH RATING	125V AC, 1A																															