

Constant Temperature

SMART SOLDERING

SQ-D60



Light and Compact

Highly Portable

Wide Range of Use



Model Number:

SQ-D60B

Dimensions:

14.5X9.5X3.5 cm

Output Temperature:

100-450°C

Output Power:

17-60w

Key Selling Points:

Accurate temperature control

Heat-up Time:

13 seconds

Input Voltage:

12-24v



SQ-D60 COMPARISON			
NO	CONTENT	A	B
1	Working Temperature	280℃, 350℃, 400℃ Three Option	100℃-400℃
2	Display	LED	Digital Tube
3	Sleep Time	Default 10 Minutes, not Adjustable	1-30 Minutes Adjustable
4	Temperature Compensation	NO	±50℃ Adjustable
5	Temperature Unit	℃	℃
6	Factory Default Temperature	280℃	300℃
7	Picture		

Internal Heating Core

Fast Efficiency/High Stability

population (the majority of respondents) is still suffering from moderate to severe depression, and this is not



Technical Parameter

Operating Voltage	Power	Fastest time to 30°C -280 °C_
12V	17W	100s
16V	30W	40s
19V	40W	22s
24V	60W	13s

Temperature Gear: Version A: 280℃, 350℃, 400℃ for Choose

VersionB: 100-400°C for Choose

Stable Temperature Range: $\pm 5^{\circ}\text{C}$

More Options

MANAGED INTELLIGENTLY



convenient



rapid heating



temperature alarm



auto sleep



adjustable temperature



wake up



DC 12V-24V supply

SOLDERING IRON PACKAGE



