



AC Rated Toggle Switches—Three-Pole

Rating	Poles and Throw	Circuit with Toggle in ...			Base Circuit See Page V11-T4-35	Bushing Length "A" Inches (mm)	Lever Length "B" Inches (mm)	Catalog Number			
		UP Position	CENTER Position	DOWN Position				Solder Lugs	Screw Terminals	0.250 in Spade Terminals	Combi-Term
15A, 125 Vac	3PST	ON	NONE	OFF	E	0.469 (11.91)	0.688 (17.48)	7700K1	7700K2	7700K3	—
10A, 250 Vac	3PDT	ON	OFF	ON	F	0.469 (11.91)	0.688 (17.48)	7701K1	7701K2	7701K3	—
3/4 hp, 250 Vac		ON	NONE	ON				7702K1	7702K2	7702K3	—
1 hp, 3 Ph											
125–600 Vac											
1 hp, 1 and 2 Ph											
125–480 Vac											
15A, 125 Vac	3PDT	MOM. ON	OFF	ON	F	0.469 (11.91)	0.688 (17.48)	7704K1	7704K2	7704K3	—
10A, 250 Vac		MOM. ON	NONE	ON				7705K1	7705K2	7705K3	—
3/4 hp, 250 Vac											
20A, 125 Vac	3PDT	ON	OFF	ON	F	0.469 (11.91)	0.688 (17.48)	7804K12	7804K32	7804K22	7804K42
10A, 250 Vac								(2)(4)	(2)	(2)	(2)
1 hp, 120 Vac											
1, 2 and 3 Ph											



AC Rated Toggle Switches—Four-Pole

Rating	Poles and Throw	Circuit with Toggle in ...			Base Circuit See Page V11-T4-35	Bushing Length "A" Inches (mm)	Lever Length "B" Inches (mm)	Catalog Number			
		UP Position	CENTER Position	DOWN Position				Solder Lugs	Screw Terminals	0.250 in Spade Terminals	Combi-Term
15A, 125 Vac	4PST	ON	NONE	OFF	E	0.469 (11.91)	0.688 (17.48)	7691K14	7690K8	—	—
10A, 250 Vac	4PDT	ON	OFF	ON	F	0.469 (11.91)	0.688 (17.48)	7693K2	7692K13	—	—
3/4 hp, 250 Vac		ON	NONE	ON				7695K5	7694K4	—	—
20A, 125 Vac	4PST	ON	NONE	OFF	E	0.469 (11.91)	0.688 (17.48)	7933K38	7933K36	7933K40	—
10A, 250 Vac	4PDT	ON	OFF	ON	F	0.469 (11.91)	0.688 (17.48)	7934K38	7934K36	7934K40	—
3/4 hp, 250 Vac		ON	NONE	ON				7935K38	7935K36	7935K40	—
1/2 hp, 125 Vac											
20A, 125 Vac	4PDT	ON	OFF	ON	F	0.469 (11.91)	0.688 (17.48)	7805K12	7805K32	7805K22	7805K42
10A, 250 Vac								(2)	(2)	(2)	(2)
1 hp, 125–240 Vac											
2 and 3 Ph											

Notes

- ① Also 1/2 hp at 125–250 Vac Rating.
 ② Not CSA Certified.
 ③ Also 7.5A, 277 Vac, 3/4 hp, 120–240–277 Vac.
 ④ 1 hp at 240–480 Vac single- or two-phase and 240–600 Vac three-phase.