

Distributed by:


JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 504701


METAL STRIP OPEN BARREL STAR RINGS WITH VIBRATION SUPPORT



Material	Order No.	Wire Size AWG (mm ²)	Stud Size S	Maximum Width W (in.)	Minimum Clearance C (in.)	Maximum Length L (in.)
Brass	19084-0001	14-18 (2.00-0.80)	6	.385	.275	.949
Brass	19084-0002	14-18 (2.00-0.80)	8	.385	.275	.949
Brass	19084-0003	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Brass	19084-0004	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Brass	19084-0005	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Brass	19084-0006	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	19084-0007	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Steel	19084-0008	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Steel	19084-0009	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	19084-0011	24 (0.20)	10	.480	.386	.965

Note: 14-18 part will accept 12 gauge wire



METAL STRIP OPEN BARREL RINGS WITH VIBRATION SUPPORT



Material	Order No.	Wire Size AWG (mm ²)	Stud Size S	Maximum Width W (in.)	Minimum Clearance C (in.)	Maximum Length L (in.)
Brass	19085-0001	14-18 (2.00-0.80)	6	.385	.275	.949
Brass	19085-0002	14-18 (2.00-0.80)	8	.385	.275	.949
Brass	19085-0003	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Brass	19085-0004	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Brass	19085-0005	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Brass	19085-0006	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	19085-0007	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Steel	19085-0008	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Steel	19085-0009	14-18 (2.00-0.80)	10	.385	.275	.949

Note: 14-18 part will accept 12 gauge wire

RING TONGUE (OFFSET)



Material: Brass or Steel				Krimptite®	
Wire Range	Stud Size S	Max. Width W	Min. Clearance C	Order No.	Max. Length L
14-12 2.0-3.0mm ²	10 (-)	.425 (10.8)	.370 (9.4)	19069-0380	.804 (20.4)

