

Distributed by:

**JAMECO**<sup>®</sup>  
ELECTRONICS

**www.Jameco.com ♦ 1-800-831-4242**

The content and copyrights of the attached  
material are the property of its owner.

Jameco Part Number 1816061

| REV | DOCUMENT | CHANGED BY  | CHECK |
|-----|----------|-------------|-------|
| 27  | 0034444  | KSR 10OCT07 | RJ    |



|             |   |
|-------------|---|
| RELEASE NO. | - |
| REPLACES    | - |

|                                   |  |                                |          |                    |  |                          |                            |  |  |                                                                                                                                                                 |        |         |                             |          |              |                    |              |
|-----------------------------------|--|--------------------------------|----------|--------------------|--|--------------------------|----------------------------|--|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|-----------------------------|----------|--------------|--------------------|--------------|
| CHARACTERISTICS                   |  | ELECTRICAL DATA                |          |                    |  | DESIGN UNITS: INCH       |                            |  |  | DRAWN                                                                                                                                                           | KSR    | 10OCT07 | <div>Honeywell</div>        |          |              |                    |              |
| OPERATING FORCE — — — — 3 - 5 OZ  |  | CONTACT ARRANGEMENT<br>S P D T |          |                    |  | TOLERANCES UNLESS NOTED: |                            |  |  | CHECK                                                                                                                                                           | RJ     | 10OCT07 |                             |          |              |                    |              |
| RELEASE FORCE— — — — 1 OZ MIN     |  | 30 VOLTS DC RATING             |          |                    |  | NO PLACE X ±             |                            |  |  | THIS DRAWING COVERS A PROPRIETARY ITEM<br>AND IS THE PROPERTY OF HONEYWELL.<br>THIS DRAWING IS NOT TO BE COPIED OR USED<br>WITHOUT THE PERMISSION OF HONEYWELL. |        |         | TITLE<br><br>SWITCH - BASIC |          |              |                    |              |
| DIFFERENTIAL TRAVEL— — — .004 MAX |  |                                |          |                    |  | ONE PLACE .X ± 0.030     |                            |  |  |                                                                                                                                                                 |        |         |                             |          |              |                    |              |
| OVERTRAVEL — — — — — .005 MIN     |  | SEA LEVEL 50,000 FT            |          |                    |  | TWO PLACE .XX ± 0.015    |                            |  |  |                                                                                                                                                                 |        |         |                             |          |              |                    |              |
|                                   |  | INDUCTIVE 3 AMP 2.5 AMP        |          |                    |  | THREE PLACE .XXX ± 0.005 |                            |  |  |                                                                                                                                                                 |        |         |                             |          |              |                    |              |
|                                   |  | RESISTIVE 5 AMP 5 AMP          |          |                    |  | FOUR PLACE .XXXX ±       |                            |  |  | INTERPRET PER ANSI Y14.5M-1982<br>OTHER HONEYWELL ENGINEERING<br>STANDARDS MAY APPLY                                                                            |        |         | SIZE                        | TYPE     | DRAWING NAME |                    | REV          |
|                                   |  | MAXIMUM INRUSH 24 AMP          |          |                    |  | ANGLES ±                 |                            |  |  |                                                                                                                                                                 |        |         | B                           | I        | 1SM1         |                    | 27           |
|                                   |  | APPROVALS                      | KEMA, CE | 5A, 250V ~ T85 1E4 |  | CE                       | THIRD ANGLE PROJECTION<br> |  |  |                                                                                                                                                                 | RASTER |         |                             | SCALE    | -            | WEIGHT .006 LB MAX | SHEET 1 OF 1 |
|                                   |  |                                | UL, CSA  | 5A, 250 VAC ~      |  | CS                       |                            |  |  |                                                                                                                                                                 |        |         |                             | BRAND L4 |              |                    |              |
|                                   |  |                                | AVIATION | FAA-PMA            |  | BRAND                    |                            |  |  |                                                                                                                                                                 |        |         |                             |          |              |                    |              |