



DS43S-480



- UL1449 TYPE 1 LISTED SPD
- MOV Technology
- 40kA Surge Current Rating
- Visual fault indicator and remote contacts
- 10-Year warranty



V: High-energy varistor
Ft: Thermal fuse
t°: Thermal disconnection system
MI: Disconnection indicator

Electrical Characteristics

Total Maximum discharge current (max. total withstand @ 8 /20 μs)	I _{max} Total	120 kA
Protection mode(s)		Common mode
POWER SPD TYPE		UL1449 TYPE 1 LISTED
VOLTS	(V)	480
AC/DC/DC PV/RF		AC
PHASE	(PH)	3D
AMPS	(A)	n/a
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+60
MODES		L-L, L-G
VPR	(V)	4000/-/1800/-
MCOV	(V)	550/-/550/-
IN(15 impulses 8/20μs)	(kA)	20
SCCR	(kA)	100
IMAX(8/20μs)	(kA)	40
Iimp(10/350μs)	(kA)	4

Option

RFI Filter		no
------------	--	----

Installation

Wiring type		Screw
Solid wire cross section(Min)	mm ²	2.5000
Solid Wire cross section(Max)	mm ²	35.0000
Stranded Wire cross section(Min)	mm ²	2.5000
Stranded wire cross section(Max)	mm ²	25.0000
Wire gauge(Min)	AWG	13.0000
Wire gauge(Max)	AWG	2.0000
Torque	Nm	2.0 - 2.5
Torque	in-lbs	17.8 - 22.1
Strip Length	mm	13.0000
Strip Length	in	0.5000
Operating Temperature(Min)	°C	-40.0000
Operating Temperature(Max)	°C	85.0000
Operating Temperature(Min)	°F	-40.0000
Operating Temperature(Max)	°F	85.0000
Operating Relative Humidity(Max)	%RH	95
Operating Altitude(Min)	Ft	2000.0000
Operating Altitude(Max)	Ft	6500.0000
Housing/Enclosure material		Thermoplastic
Flammability rating(UL 94)		V0
Mounting		Din Rail
IP Environmental rating(IP)		IP20
NEMA Environmental rating(NEMA)		NEMA 1
Installation Location		Indoor
Spare part		Module
Product Dimension(L)	mm	99.0000
Product Dimension(H)	mm	67.0000

DS43S-480

Product Dimension(W)	mm	54.0000
Product Dimension(L)	In	3.8900
Product Dimension(H)	In	2.6400
Product Dimension(W)	In	2.1300
Miscellaneous		
Individual Pack		Yes
Storage Temperature(Min)	°C	-40.0000
Storage Temperature(Max)	°C	85.0000
Storage Temperature(Min)	°F	-40.0000
Storage Temperature(Max)	°F	85.0000
Storage Relative Humidity(Max)	%RH	95.0000
Mechanical Characteristics		
Weight		0.31 kg
TECHNOLOGY		MOV
NETWORK CONFIGURATION		3PH, 3W+G, Delta
CONNECTION METHOD		Screw Terminal (8-12AWG)
MOUNTING		DIN RAIL
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts
DIMENSIONS		See diagram (mm)
WEIGHT		0.90 lbs
SPARE PART		DSM40-480
Standards		
Certification		UL / CSA / EAC
UL STANDARD		UL1449 5th Edition
UL CATEGORY		VZCA, VZCA7
UL FILE NUMBER		E326289
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Part number		
461017		