



- 1 Pair Protection
- Modes of Protection L-L,L-G
- Conduit Mounting
- Direct Transducer Mount
- Parallel or Series Connection Options

| Electrical Characteristics        |      |                  |
|-----------------------------------|------|------------------|
| VOLTS                             | (V)  | 48               |
| WIRES                             |      | 4W+GROUND        |
| LINE CURRENT MAX                  | (A)  | 0.3              |
| AMBIENT MIN                       | (C)  | -55              |
| AMBIENT MAX                       | (C)  | +85              |
| IN15 impulses 8/20µs              | (kA) | 10               |
| IMAX8/20µs                        | (kA) | 15               |
| label.propertyGroup.INSTALLATION  |      |                  |
| Operating Relative HumidityMax    | %RH  | Can be submerged |
| Operating AltitudeMin             | Ft   | 2000.0000        |
| Operating AltitudeMax             | Ft   | 6500.0000        |
| Housing/Enclosure material        |      | Stainless Steel  |
| Mounting                          |      | Side mount       |
| Installation Location             |      | Indoor / outdoor |
| Product DimensionL                | mm   | 114.3000         |
| Product DimensionH                | mm   | 26.0000          |
| Product DimensionW                | mm   | 27.9400          |
| Product DimensionL                | In   | 4.5000           |
| Product DimensionH                | In   | 1.0000           |
| Product DimensionW                | In   | 1.1000           |
| Product Weight                    | lbs  | 0.8000           |
| label.propertyGroup.MISCELLANEOUS |      |                  |
| Individual Pack                   |      | Yes              |
| Part number                       |      |                  |
| 6339                              |      |                  |