

Model 73084, 73085, 73086, 73088

Terminal Jacks, Male Threads 6-32, 8-32, 10-32, Female Threads 10-32

Features

- Adapter provides an easy and quick banana jack connection by replacing the screw in a terminal strip or control panel.
- Allows a standard sheathed or unsheathed banana plug / patch cord to securely connect to a terminal strip.
- Helps to avoid accidental arc-over by eliminating the usage of alligator clips, or test probe "slip offs" during measurement applications.
- Perfect for use with model **73087** jumper test lead sets in *peer-checking* system test sequences.
- For more information, please visit our "**Articles**" section on nuclear applications at www.pomonaelectronics.com.

**Materials**

Banana Jack:

Nickel-plated Brass

Insulation:

Polypropylene

Specifications

Voltage:

600 Vrms, Maximum voltage for *hands free use*.For *CE compliance*, do not hold in hand when voltages exceed 33 Vrms / 70 Vdc

Current:


20 A

Operating Temperature:

-10° C to +80° C (+14° F to 176° F)




Torque In/Lb.:

73084:	7
73085:	20
73086:	20
73088:	16

Dimensions**Model 73086, 10-32 Female Terminal Jack**

USA: Sales: 800-490-2361
Technical Support: technicalsupport@pomonatest.com
Fax: 425-446-5844
Europe: 31-(0) 40 2675 150 **International:** 425-446-5500
Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = ± 0.02 " (.51 mm), .xxx = ± 0.005 " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Model 73084, 73085, 73086, 73088**Terminal Jacks, Male Threads 6-32, 8-32, 10-32, Female Threads 10-32****Model 73084, 6-32 Male Terminal Jack****Model 73088, 8-32 Male Terminal Jack****Model 73085, 10-32 Male Terminal Jack****Ordering Information**Model: **73084, 73085, 73086, 73088**

Standard Colors: -0 Black, -2 Red, -4 Yellow, -6 Blue

Ordering Example: **73084-2**, (73084 terminal jack with Red insulation)

USA: Sales: 800-490-2361
Technical Support: technicalsupport@pomonatest.com
Fax: 425-446-5844

Europe: 31-(0) 40 2675 150 **International:** 425-446-5500

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = ± 0.02 " (.51 mm), .xxx = ± 0.005 " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.