

UL Style 1015/1028 Hook-up Wire

Product Details:

- Available in Tin Copper, Bare Copper, or Topcoat
- PVC (Polyvinylchloride) Insulation, 105°C, 600V: UL 1032 1000V
- MTW AWM 1015, 1028, 1032, 1230, 1231, 1335 VW-1 FT-1 TEW
- Exceptions: MTW only on stranded 22 AWG or larger

Color Code:

- 0: Black
- 1: Brown
- 2: Red
- 3: Orange
- 4: Yellow
- 5: Green
- 6: Blue
- 7: Violet
- 8: Gray
- 9: White

Custom colors and striping available upon request.

Part Number	Construction	Insulation	Insulation (in)	Nom. OD (in)	Temp.	Volt.	Product Type
10288133B	8 (133x29) BC	PVC	.045	.252	105	600	1028 / 1032 / 1231
1028819B	8 (19x.0295) BC	PVC	.045	.237	105	600	1028 / 1032 / 1231
894	8 (133x29) TC	PVC	.045	.252	105	600	1028 / 1032 / 1231
101510105B	10 (105X30) BC	PVC	.030	.180	105	600	1015 / 1230 / 1335 / 1032
1015101T	10 (Solid) TC	PVC	.030	.164	105	600	1015 / 1230 / 1335 / 1032
893	10 (105x30) TC	PVC	.030	.180	105	600	1015 / 1230 / 1335 / 1032
1015121T	12 (Solid) TC	PVC	.030	.144	105	600	1015 / 1230 / 1335 / 1032
10151265B	12 (65X30) BC	PVC	.030	.157	105	600	1015 / 1230 / 1335 / 1032
892	12 (65x30) TC	PVC	.030	.155	105	600	1015 / 1230 / 1335 / 1032
10151441B	14 (41x30) BC	PVC	.030	.136	105	600	1015 / 1230 / 1335 / 1032
863	14 (Solid) TC	PVC	.030	.124	105	600	1015 / 1230 / 1335 / 1032
891	14 (41x30) TC	PVC	.030	.136	105	600	1015 / 1230 / 1335 / 1032
10151626B	16 (26x30) BC	PVC	.030	.117	105	600	1015 / 1230 / 1335 / 1032
862	16 (Solid) TC	PVC	.030	.111	105	600	1015 / 1230 / 1335 / 1032
890	16 (26x30) TC	PVC	.030	.117	105	600	1015 / 1230 / 1335 / 1032
10151816B	18 (16X30) BC	PVC	.030	.108	105	600	1015 / 1230 / 1335 / 1032
861	18 (Solid) TC	PVC	.030	.102	105	600	1015 / 1230 / 1335 / 1032
876	18 (16x30) TC	PVC	.030	.106	105	600	1015 / 1230 / 1335 / 1032
885	18 (16x30) F	PVC	.030	.108	105	600	1015 / 1230 / 1335 / 1032
10152010B	20 (10x30) BC	PVC	.030	.099	105	600	1015 / 1230 / 1335 / 1032
856	20 (Solid) TC	PVC	.030	.098	105	600	1015 / 1230 / 1335 / 1032
871	20 (10x30) TC	PVC	.030	.099	105	600	1015 / 1230 / 1335 / 1032
875	20 (7x28) F	PVC	.030	.100	105	600	1015 / 1230 / 1335 / 1032
1015227B	22 (7x30) BC	PVC	.030	.095	105	600	1015 / 1230 / 1335 / 1032
851	22 (Solid) TC	PVC	.030	.091	105	600	1015 / 1230 / 1335 / 1032

Part Number	Construction	Insulation	Insulation (in)	Nom. OD (in)	Temp.	Volt.	Product Type
865	22 (7x30) F	PVC	.030	.095	105	600	1015 / 1230 / 1335 / 1032
866	22 (7x30) TC	PVC	.030	.091	105	600	1015 / 1230 / 1335 / 1032
866-24	24 (7x32) TC	PVC	.030	.086	105	600	1015 / 1230 / 1335 / 1032
851-24	24 (Solid) TC	PVC	.030	.083	105	600	1015 / 1230 / 1335 / 1032
866-26	26 (7x34) TC	PVC	.030	.081	105	600	1015 / 1230 / 1335 / 1032

Note: All specifications are subjected to change without prior notice.