

# AR14126CHFL



Sample image

**Order symbol :** AR14126CHFL

**Product nr :** 8561692

**Description :** PC Enclosure

**Remarks :** Hinged opaque flat cover w/Plastic quick release latch.

**EAN :** 6418074098658

**Including :** Hinged cover. Base with 10-32 brass inserts, latched flat cover with formed in place PUR gasket, and stainless hinge pin. Quick release latches. (Latch options available.). Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

| Dimensions : | Height | Width | Depth |
|--------------|--------|-------|-------|
| mm :         | 356    | 305   | 152   |
| inch :       | 14     | 12    | 6     |

## Materials :

|                   |                      |
|-------------------|----------------------|
| Material :        | Polycarbonate        |
| Base colour :     | RAL 7035 -light grey |
| Cover colour :    | RAL 7035 -light grey |
| Gasket material : | Polyurethane         |

## Temperatures :

|                               |             |
|-------------------------------|-------------|
| Temperature °C (short term) : | -40 ... 140 |
| Temperature °C (continuous) : | -40 ... 80  |
| Temperature °F (short term) : | -40 ... 250 |
| Temperature °F (continuous) : | -40 ... 175 |

## Accessories :

|          |                             |
|----------|-----------------------------|
| ABP1412  | Painted Steel Back Panel    |
| ASP1412  | Aluminum Swing Panel        |
| ASPHK14  | Swing Panel Kit w/o Panel   |
| AMFL12   | 12" Mounting Flange Set     |
| ADFP1412 | Dead Front Panel w/ screws  |
| ALBP1412 | Aluminum Back Panel         |
| APBP1412 | PVC Back Panel              |
| ASPK1412 | Swing Panel Kit incl. Panel |

## Ratings :

|                                         |                       |
|-----------------------------------------|-----------------------|
| Ingress protection (EN 60529):          | IP66; IP67;           |
| Impact Resistance (EN 62262):           | IK09;                 |
| electrical_insulation :                 | Totally insulated     |
| Halogen free (DIN/VDE 0472, Part 815) : | Yes                   |
| UV resistance :                         | UL 508                |
| Flammability Rating :                   | UL 508                |
| Glow Wire Test (IEC 695-2-1) °C :       | 960 °C                |
| NEMA Class                              | NEMA 4, 4X, 12 and 13 |