

YS16V-U SERIES



Input: 85-265VAC 50/60Hz
Output Voltage: 5V-36V DC
Rated Power: 18W max

Features


Univeral AC input/ Full range
 Energy efficiency level VI
 Leakage Current: < 0.25mA
 Extremely low leakage current
 Protection: Over load/Over voltage/Short circuit
 Withstand voltage : 3KV
 Life Warranty: 3 years

Application

Digital equipment
 Consumer electronic devices
 Telecommunication devices
 Office facilities
 Industrial equipments



■ Dimensions and Installation




YS16V-U SERIES


MODEL DETAIL SPEC.		YS16V-0503000	YS16V-0902000	YS16V-1201500	YS16V-1501600	YS16V-2400750	YS16V-3600500
INPUT	Input Voltage:	85-265VAC					
	Input Frequency:	50/60Hz					
	Inrush Current:	15A/115VAC 30A/230VAC					
	AC Current:	0.6A/115VAC 0.3A/230VAC					
	Leakage Current:	< 0.25mA/240VAC					
	Efficiency:	81%	85%	86%	87%	87%	88%
OUTPUT	DC Voltage:	5V	9V	12V	15V	24V	36V
	Rated Current:	3A	2A	1.5A	1.6A	0.75A	0.5A
	Rated Power:	15W	18W	18W	18W	18W	18W
	Voltage Tolerance:	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%
	Ripple and Noise:	75mVp-p	90mVp-p	120mVp-p	150mVp-p	240mVp-p	300mVp-p
	Line Regulation:	±3%					
	Load Regulation:	±5%	±5%	±5%	±5%	±5%	±5%
	Setup, Rise, Hold Up time:	500ms, 30ms/120ms 230VAC 1000ms, 30ms/25ms 115VAC at full load					
ENVIRONMENTAL	Operating Temperature:	-20 ~ +60 (Refer to "Derating Curve")					
	Storage Temp:	-40℃ ~ 85℃					
	Storage Humidity:	10 ~ 95% RH					
	Working Humidity:	20 ~ 95% RH non-condensing					
PROTECTION	Over Load:	105% -150% rated output power					
		Protection type: Hiccup mode, recovers automatically after fault condition is removed					
	Over Voltage:	105% -130% rated output power					
		Protection type: Shut down o/p voltage, re-power on to recover					
	Short Circuit :	Shut down o/p voltage, re-power on to recover					
SAFETY & EMC	Safety Regulations:	UL62368-1 approved					
	Withstand Voltage:	I/P-O/P:3KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC					
	Isolation Resistance:	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25℃/ 70% RH					
	EMC Emission:	FCC Part15/CISPR22, CAN ICES-3(B) NMB-3(B), Class B					
	EMC Immunity:	FCC Part15/CISPR22, CAN ICES-3(B) NMB-3(B), Class B					
OTHER	MTBF:	100Khrs min. MIL-HDBK-217F(25℃)					
	Size:	70*33*80mm					
	Weight:	120g / pcs					
	Packaging:	100PCS/CTN					

YS16V-U SERIES

Deduction curve
and temperature





Minus output
and input voltage curves











DC output plug

Standard plug: D1M

D1M			Pin Assignment	
				
			Outside	Inside
			-V not connected to AC FG(standard) -V connected to AC FG(optional)	


YS18V-U SERIES

Optional DC plug: (Available in customized cable or quick adapter)

Tuning Fork Style		Type No.	A	B	C	Quick Adapter Accessory
			OD	ID	L	
   (Straight)  (Right-angled)	D1I	5.5	2.1	9.5	Available (Current rating: 7.5A max.)	
	D1L	5.5	2.5	9.5		
	D1M	5.5	2.1	11.0		
	D1IR	5.5	2.5	9.5		
	D1JR	5.5	2.1	11.0		
	D1LR	5.5	2.5	9.5		
	D1MR	5.5	2.5	11.0		
Barrel Style		Type No.	A	B	C	Quick Adapter Accessory
			OD	ID	L	
   (Straight)  (Right-angled)	D2I	5.5	2.1	9.5	None	
	D2J	5.5	2.1	11.0		
	D2L	5.5	2.5	9.5		
	D2M	5.5	2.1	11.0		
	D2IR	5.5	2.5	9.5		
	D2JR	5.5	2.1	11.0		
	D2LR	5.5	2.5	9.5		
D2MR	5.5	2.5	11.0			
Lock Style		Type No.	A	B	C	Quick Adapter Accessory
			OD	ID	L	
   Floating Locking SWITCHCRAFT original or equivalent	D2S(S761K)	5.53	2.03	12.06	None	
	D2K(761K)	5.53	2.54	12.06		
	D2C(S760 K)	5.53	2.03	9.52		
	D2D(760K)	5.53	2.54	9.52		
Center Pin Style		Type No.	A	B	C	Quick Adapter Accessory
			OD	ID	L	
   EIAJ equivalent	D4A	5.5	3.4	11.0	1.0	Available (Current rating: 7.5A max.)
	D4B	6.5	4.4	11.0	1.4	
	D4C	7.4	5.1	11.0	0.6	
Min. Pin Style		Type No.	A	B	C	Quick Adapter Accessory
			OD	ID	L	
   EIAJ equivalent	D3A	2.35	0.7	11.0	Available (Current rating: 5A max.)	
	D3B	4.0	1.7	11.0		
	D3C	4.75	1.7	11.0		

YS18V-U SERIES

Optional DC plug: (Available in customized cable or quick adapter)

Min.Din 3Pin with Lock (male)	Type No.	Pin Assignment		Quick Adapter Accessory
		PIN No.	Output	
   KYCON KPPX-3P equivalent	M6B	1	+Vo	Available (Current rating: 7.5A max.)
		2	-Vo	
		3	+Vo	
Min.Din 4Pin with Lock (male)	Type No.	Pin Assignment		
		PIN No.	Output	
   KYCON KPPX-4P equivalent	M7B	PIN No.	Output	Available (Current rating: 7.5A max.)
		1	+Vo	
		2	-Vo	
		3	-Vo	
		4	+Vo	
Min.Din 4Pin with Lock (female)	Type No.	Pin Assignment		
		PIN No.	Output	
   KYCON KPJX-CM-4S equivalent	M7BF	PIN No.	Output	None
		1	+Vo	
		2	-Vo	
		3	-Vo	
		4	+Vo	
DIN 5Pin (male)	Type No.	Pin Assignment		
		PIN No.	Output	
  	M1B	PIN No.	Output	Available (Current rating: 7.5A max.)
		1	-Vo	
		2	-Vo	
		3	+Vo	
		4	-Vo	
		5	+Vo	
Stripped and tinned leads	Type No.	Pin Assignment		
		PIN No.	Output	
	by customer	1	+Vo	None
		2	-Vo	