



PST-240 Series Specifications



Features:

- Three-Phase AC 340 ~ 550V wide range input
- High efficiency 89% and low dissipation
- Protections: Short Circuit / Overload / Overvoltage / Over temperature
- Cooling by free air convection
- Built-in constant current limiting circuit
- DIN rail mountable
- UL 508(industrial control equipment)approved
- EN61000-6-2(EN50082-2) industrial immunity level
- 100% full load burn-in test
- Fixed switching frequency at 70KHz
- 3 year warranty

OUTPUT

Cat. No.	PST-24024	PST-24048
DC VOLTAGE	24V	48V
RATED CURRENT	10A	5A
CURRENT RANGE	0 ~ 10A	0 ~ 5A
RATED POWER	240W	240W
RIPLLE & NOISE (max)	80mVp-p	80mVp-p
VOLTAGE ADJ. RANGE	24 ~ 28V	48 ~ 55V
VOLTAGE TOLERANCE	±1.0%	±1.0%
LINE REGULATION	±0.5%	±0.5%
LOAD REGULATION	±0.5%	±0.5%
SETUP, RISE, HOLD UP TIME	1200ms, 40ms, 20ms / 400VAC; 800ms, 40ms, 40ms / 500VAC at full load	

INPUT

VOLTAGE RANGE	Three Phase 340 ~ 550VAC (Dual Phase operation possible) 480 ~ 780VDC Dual phase operation: derating of 20% is required
FREQUENCY RANGE	47 ~ 63Hz
EFFICIENCY (Typ.)	89%
AC CURRENT	0.95A / 400VAC; 0.75 / 500VAC
INRUSH CURRENT (Typ.)	COLD START 50A
LEAKAGE CURRENT	≤ 3.5 mA / 530VAC
OVERLOAD	105 ~ 150% rated output power Protection type: Constant current limiting, recovers automatically after fault condition is removed
OVERVOLTAGE	30 ~ 36V 59 ~ 66V Protection type: Shut down overvoltage, re-power on to recover
OVERTEMPERATURE	100°C ± 5°C (TSW) detect on heat sink of power switch Protection type: Shut down overvoltage, re-power automatically after temperature goes down

ENVIRONMENT

WORKING TEMP.	-20 ~ +70°C (Refer to output load derating curve)
WORKING HUMIDITY	20 ~ 90% RH non-condensing
STORAGE TEMP., HUMIDITY	-40 ~ +85°C, 10 ~ 95% RH
TEMP. COEFFICIENT	±0.03% / °C (0 ~ 50°C)
VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, 60 min. each long X,Y, Z axes
Mounting	Compliance to IEC60068-2-6


SAFETY & EMC

SAFETY STANDARDS	UL508 EN60950-1 compliant UL60950-1 I/P-O/P: 3KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC I/P-O/P, I/P-FG, O/P-FG: 100M Ohms / 500VDC (25°C; 70% RH) Compliance to EN55011 (CISPR11), EN55022 (CISPR22) Class B Compliance to EN61000-4-2,3,4,5,6,8,11; ENV50204; EN61000-6-2; (EN50082-2), EN61204-3; heavy industry level; criteria A, The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.
MTBF DIMENSION PACKING	114.6K hrs min. MIL-HDBK-217K (25°C) 125.5x125.2x100mm (WxHxD) 1.3Kg; 12pcs / 16.6Kg / 1.29CUFT All parameters NOT specially mentioned are measured at 400VAC input, rated load and 25°C of ambient temperature.

OTHERS

For the latest on Altech Power Supply specifications please visit www.altechcorp.com/power.

Mechanical Specification




TB1 Terminal Pin. No Assignment

Pin No.	Assignment
1	FG (GND)
2	AC/L3
3	AC/L2
4	AC/L1


TB2 Terminal Pin. No Assignment

Pin No.	Assignment
1,2	DC OUTPUT +V
3,4	DC OUTPUT -V


Block Diagram



Derating Curve



Output Derating VS Input Voltage



Note: All dimensions are in millimeters, to convert to inches multiply by 0.03937.