


RoHS Compliant

# UC-146/ UC-157

## uPCI 1xLPT Printer Port

"PARALLEL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



### Features

- 1xLPT Printer
- Standard Profile or Low Profile Option
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

### Options

UC-146:  
uPCI 1xLPT Printer Port



UC-157:  
LP uPCI 1xLPT Printer Port



### Description

Universal PCI card providing one standard height LPT port .Includes drivers for all Windows 32 bit and 64 bit Operating Systems, including Windows 7.

Available as standard profile or low profile card. Low profile is the industry standard small form factor design for PCI. UC-146 - Standard profile version; UC-157 - Low Profile version.

Universal PCI is fully compatible with both 3.3Volt and 5Volt PCI slots; protecting your investment into the future.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit & 64 bit Editions
- Windows Server 2008 32 bit & 64 bit Editions
- Windows Vista 32 bit & 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions



As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.



### ORDER

#### Description

- uPCI 1xLPT Printer Port
- LP uPCI 1xLPT Printer Port


#### Code

- UC-146
- UC-157



# uPCI 1xLPT Printer Port

UC-146/ UC-157: Full Specification

Port	Ports	1																																																												
	Connector	25 Pin Parallel Port Female Connector																																																												
		<table border="1"> <thead> <tr> <th>Pin No</th> <th>Signal</th> <th>Direction</th> <th>Pin No</th> <th>Signal</th> <th>Direction</th> </tr> </thead> <tbody> <tr><td>1</td><td>Data Strobe</td><td>in/out</td><td>10</td><td>ACK</td><td>in</td></tr> <tr><td>2</td><td>Data 0</td><td>out</td><td>11</td><td>Busy</td><td>in</td></tr> <tr><td>3</td><td>Data 1</td><td>out</td><td>12</td><td>Paper out</td><td>in</td></tr> <tr><td>4</td><td>Data 2</td><td>out</td><td>13</td><td>Select</td><td>in</td></tr> <tr><td>5</td><td>Data 3</td><td>out</td><td>14</td><td>Auto feed</td><td>in/out</td></tr> <tr><td>6</td><td>Data 4</td><td>out</td><td>15</td><td>Error</td><td>in</td></tr> <tr><td>7</td><td>Data 5</td><td>out</td><td>16</td><td>Init</td><td>in/out</td></tr> <tr><td>8</td><td>Data 6</td><td>out</td><td>17</td><td>Select Input</td><td>in/out</td></tr> <tr><td>9</td><td>Data 7</td><td>out</td><td>18-25</td><td>GND</td><td></td></tr> </tbody> </table>	Pin No	Signal	Direction	Pin No	Signal	Direction	1	Data Strobe	in/out	10	ACK	in	2	Data 0	out	11	Busy	in	3	Data 1	out	12	Paper out	in	4	Data 2	out	13	Select	in	5	Data 3	out	14	Auto feed	in/out	6	Data 4	out	15	Error	in	7	Data 5	out	16	Init	in/out	8	Data 6	out	17	Select Input	in/out	9	Data 7	out	18-25	GND	
Pin No	Signal	Direction	Pin No	Signal	Direction																																																									
1	Data Strobe	in/out	10	ACK	in																																																									
2	Data 0	out	11	Busy	in																																																									
3	Data 1	out	12	Paper out	in																																																									
4	Data 2	out	13	Select	in																																																									
5	Data 3	out	14	Auto feed	in/out																																																									
6	Data 4	out	15	Error	in																																																									
7	Data 5	out	16	Init	in/out																																																									
8	Data 6	out	17	Select Input	in/out																																																									
9	Data 7	out	18-25	GND																																																										
General	Bracket Profile	Standard Profile (UC-146) / Low Profile (UC-157)																																																												
	PCB Layers	4																																																												
	Power Consumption	195mA @ 5V / 15mA @ 12V (UC-146) 195mA @ 5V, 15mA @ 12V (UC-157)																																																												
	Weight	0.067 kg, 0.15 pounds (UC-146) 0.063 kg, 0.14 pounds (UC-157)																																																												
	Size	null																																																												
Interface	OS Compatibility	Windows 7 32 bit & 64 bit Editions Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions Windows Server 2003 32 bit & 64 bit editions Windows XP 32 bit & 64 bit editions																																																												
PCI	BUS	PCI 3.0																																																												
Approvals	Other Approvals	AEO (C-TPAT) Microsoft Certified Gold Partner WEEE RoHS																																																												
  	Microsoft Approvals	Microsoft Certified Gold Partner Windows 7 32 bit & 64 bit Editions Windows Server 2008 32 bit & 64 bit Editions Windows Vista 32 bit & 64 bit editions Windows Server 2003 32 bit & 64 bit Editions																																																												
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities																																																												
	Card	uPCI 1xLPT Printer Port																																																												
Product Support	Warranty	Lifetime (online registration required)																																																												
 	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team																																																												
Additional	OEM option	Available for bulk buy OEM																																																												
 	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"																																																												
	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com																																																												

Other PCI Cards: 1xRS232 | 2xRS232 | 4xRS232 | 8xRS232 | 1xRS422/485 | 2xRS422/485 | 4xRS422/485

Other Brainboxes Ranges: PCI Express | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial