

Universal Ferrule Crimpers for Original Ferrules

Front and Side Conductor Entry

Crimpers work with a wide range of insulated and uninsulated ferrule sizes. Universal Ferrule Crimpers are offered to crimp different ferrule and wire size ranges up to 500MCM).

- Positive ratcheting with spring return
- Trapezoidal and square crimp geometry
- Comfort grip plastic handle
- Hardened steel frame

Universal Ferrule Crimper Trapizodial Crimp



Part No.	Wire/ AWG	Ferrule mm ²
E550.000	28 - 6 2x24 - 2x8	0.08 - 16 2x.25 - 2x10.0

1851-6300 Replacement Trapezoidal Die

Universal Ferrule Crimper Square Crimp



Part No.	Wire/ AWG	Ferrule mm ²
E660.000	28 - 6 2x24 - 2x8	0.08 - 16 2x.25 - 2x10.0

1851-6200 Replacement Square Die

Universal Ferrule Crimper Square Crimp



Part No.	Wire/ AWG	Ferrule mm ²
014473	8 - 0 (1/0)	10 - 50
014474	0 (1/0) - 000 (3/0)	50 - 95

Larger Ferrule Crimpers

Individual crimp cavities conform to industry standard insulated and uninsulated ferrules from 1 - 500 MCM AWG 50-500mm²)

- Positive ratcheting with spring return
- Trapezoidal crimp geometry
- Comfort grip plastic handle
- Hardened steel frame

Large Ferrule Crimper Crimping Die-Sets Sold Separately



Handle Only without Die Set

008878 CE 240

Die-Set	Part No.	Wire Size	
008880	CE E50	1 AWG	50 mm ²
008881	CE E70	2/0 AWG	70 mm ²
008882	CE E95	3/0 AWG	95 mm ²
008883	CE E120	4/0 AWG	120 mm ²
009204	CE E150	250 MCM	250 mm ²
008884	CE E185	350 MCM	350 mm ²
008885	CE E240	500 MCM	500 mm ²

Lighter Duty Ferrule Crimping Pliers




Ferrule Crimping Pliers with Ratched Cycle

Part No.	For Wire Sizes
Crimpit 05 Z	26-20 AWG (0.14-0.5 mm ²)
Crimpit 2.4 Z	20-14 AWG (0.5-2.5 mm ²)

Ferrule Crimping Pliers without Ratched Cycle

Part No.	For Wire Sizes
Crimpit 05	26-20 AWG (0.14-0.5 mm ²)
Crimpit 2.4	20-14 AWG (0.5-2.5 mm ²)

Vise Mount Ferrule Crimper



Part No.	Wire/ AWG	Ferrule mm ²
22.030	2/0-250 MCM	70 - 150