



Quality Products. Service Excellence.

Rack Mount Basic PDU 1582E DP Series

10A Double Pole | Single-Phase 100-240V | Front or Rear Facing C13 Outlets

Features

- On-Off switch is rocker type (double pole, single throw) with green light.
- Rated 100-240VAC (TUV), 120-240VAC (UL), 10A, 50/60Hz
- Designed for power distribution on front or rear of unit with IEC power cords.
- 1U horizontal 19" rackmount installation.
- All steel housing with black powder coat finish.



Specifications

- Includes 10A circuit breakers to prevent accidental line overload.
- cULus Listed UL 62368-1 (2nd Edition), 2014-12-01, and CAN/CSA C22.2 No. 62368-1-14 (2nd Edition).
- TÜV-SUD Certified to EN 62368-1:2014/A11:2017, and IEC 62368-1:2014 (2nd Edition)
- TÜV-SUD tested for EMC Compliance to EN 55032:2012 (CISPR 32:2012) & EN 55024:2010 (CISPR 24:2010).
- CE compliant to the European Low Voltage Directive 2014/35/EU.
- CE compliant to the European EMC Directive 2014/30/EU.
- UKCA compliant to British Electrical Equipment (Safety) Regulations 2016 (S.I. 2016/1101)
- UKCA compliant to British Electromagnetic Compatibility Regulations 2016 (S.I. 2016/1091)
- TAA compliant for GSA Schedule purchases.
- RoHS Compliant.
- Manufactured in North America.



Accessories

- Mounting Hardware
- Rail Depth Adapter Kit
- Power Cords

| With Illuminated On/Off Switch Part No. | Overall Dimensions | | | Number of Outlets | | Outlet Type | Inlet Type | Inlet Location |
|---|--------------------|-------|-------|-------------------|------|----------------|---------------|-------------------|
| | Height | Width | Depth | Front | Rear | | | |
| 1582H8E1BKDP | 1.72 | 19.00 | 2.66 | 8 | 0 | C13 | C14 | Rear |
| 1583H8E1BKDP | 1.72 | 19.00 | 2.66 | 0 | 8 | C13 | C14 | Rear |

Data subject to change without notice

© 2023. Hammond Manufacturing Ltd. All rights reserved.