

Distributed by:

JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 302658

AMP**PIDG Terminals****PIDG Ring Tongue Terminals****Material and Finish****Insulation** — Nylon**Terminal Body and Metallic****Sleeve** — Copper per ASTM B-152,
tin plated per MIL-T-10727

Wire Size Circular Mills [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
26-22 202-810 [0.10-0.41]	0.51 .020	2 M2	3.56 .140	Yellow	2.08 .082	323912*
		4	5.16 .203	Yellow	2.08 .082	323914*
		6 M3.5	5.16 .203	Yellow	2.08 .082	323915*
		8 M4	6.35 .250	Yellow	2.08 .082	323916*
		10	6.35 .250	Yellow	2.08 .082	324075*
22-16 509-3,260 [0.26-1.65]	0.84 .033	2 M2	5.54 .218	Red	3.18 .125	328657*
		4	5.54 .218	Red	3.56 .140	31880*
		6 M3.5	7.14 .281	Red	3.56 .140	36152*
		8 M4	7.92 .312	Red	3.56 .140	31890*
		10	7.92 .312	Red	3.56 .140	36154*
		1/4 M6	11.91 .469	Red	3.56 .140	31894*
		5/16 M8	11.91 .469	Red	3.56 .140	31895*
		3/8	13.49 .531	Red	3.56 .140	31897*
16-14 2,050-5,180 [1.04-2.62]	0.84 .033	4	6.35 .250	Blue	4.32 1.70	328996*
		6 M3.5	6.35 .250	Blue	4.32 1.70	320619*
		8 M4	8.71 .343	Blue	4.32 1.70	320565*
		10	8.71 .343	Blue	4.32 1.70	36160*
		1/4 M6	11.91 .469	Blue	4.32 1.70	321045*
		5/16 M8	11.91 .469	Blue	4.32 1.70	328998*
		3/8	13.49 .531	Blue	4.32 1.70	328999*
16-14D [†] 2,050-5,180 [1.04-2.62]	1.27 .050	8 M4	8.71 .343	Yellow/Blk.	5.84 .230	320627*
		10	8.71 .343	Yellow/Blk.	5.84 .230	320630*

*Available in small packaging quantities.

†Heavy duty for extra mechanical strength.





PIDG Terminals (Continued)

PIDG Ring Tongue Terminals (Continued)

Material and Finish

Insulation — Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152,
tin plated per MIL-T-10727

Wire Size Circular Mills [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
12-10 5,180-13,100 [2.62-6.64]	1.07 .042	6 M3.5	7.14 .281	Yellow	6.35 .250	35149*
		8 M4	9.53 .375	Yellow	6.35 .250	35108*
		10	9.53 .375	Yellow	6.35 .250	35109*
		1/4 M6	13.49 .531	Yellow	6.35 .250	35110*
		15/16 M8	13.49 .531	Yellow	6.35 .250	35111*
		3/8	15.06 .593	Yellow	6.35 .250	35112*
		1/2 M12	19.05 .750	Yellow	6.35 .250	35151*

*Available in small packaging quantities.



PIDG Spade Tongue Terminals

Material and Finish

Insulation — Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152,
tin plated per MIL-T-10727

Wire Size Circular Mills [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
22-16 509-3,260 [0.26-1.65]	0.84 .033	2 M2	4.62 .182	Red	3.56 .140	328394*
		4	5.54 .218	Red	3.56 .140	327717*
		6 M3.5	6.35 .250	Red	3.56 .140	34541*
		8 M4	9.53 .375	Red	3.56 .140	32053*
		10	9.53 .375	Red	3.56 .140	32054*
16-14 2,050-5,180 [1.04-2.62]	0.84 .033	6 M3.5	7.54 .297	Blue	4.32 .170	35559*
		8 M4	9.78 .385	Blue	4.32 .170	32059*
		10	9.78 .385	Blue	4.32 .170	32060*
12-10 5,180-13,100 [2.62-6.64]	1.07 .042	10	10.31 .406	Yellow	5.84 .230	32589*

*Available in small packaging quantities.



Power

Terminals and Miscellaneous