

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 495816

-
- Home
 - Part Number Search
 - Document Search
 - CAD Model Search
 - Text Search
 - Alternate/Lead Free Part Search
 - Multiple Part Comparison
 - Alphabetical Search
 - Brand Search
 - Industry Product Search
 - Product Type Search
 - Product Family Search
 - Competitor Cross Reference
 - Lead Free Solutions
 - Tool Search
 - Help/Glossary

Soft Shell Connectors

.250" Centerline, 600 V, 19 - 36 A max. (Universal MATE-N-LOK)

AMP350689-1ActiveActiveRoHS CompliantRoHS Compliant

(Tyco Electronics P/N: 350689-1)

CAD Geometry | Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
General Info Sales Info Assembly Subcontractors	Pricing Product Availability	Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

Product Photo

Searchable Features:		Other Properties:	
Brand:	AMP	RoHS/ELV Compliance History:	Always was compliant
RoHS/ELV Compliance:	RoHS compliant, ELV compliant	Contact Diameter (mm [in]):	2.13 [0.084]
Lead Free Solder Process:	Not relevant for lead free process	Stock Thickness (mm [in]):	0.25 [0.010]
Product Type:	Contact	Voltage (VAC):	600
Connector Line:	Universal MATE-N-LOK	Packaging Method:	Loose Piece
CompactPCI:	No	Contact Termination Area Plating:	Pre-Tin
Contact Type:	Socket		
High Current:	No		
Wire Range (mm [AWG]):	0.20-0.80 ² [24-18]		

Insulation Diameter (mm [in]):	1.02-2.54 [.040-.100]
Contact Material:	Brass
Sealable:	No
Current Rating (Amps.):	19

Comment:

Contacts can be used with Splash Proof Seals if insulation diameter range is .060-.100.

[Copyright](#) and [Privacy Statement](#)

Visit [Tyco International, Ltd.](#)

[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)

i2 Technologies US, Inc.

HTML Pages converted to PDF Document

This document contain component information from the manufacturer's website which are not available in a revision controlled document from the manufacturer. To facilitate the addition of these parts into the Electronics Database, we are converting the HTML pages related to that part, from the manufacturer's website into Adobe PDF format. The contents of this document is based on the information provided on the manufacturer's website, therefore the information may have been changed by the manufacturer since this was created.

