

Distributed by:

JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 568771

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 5014C
Page 1 of 1 Pages

Issue: 4
Issue Date: 11/5/2003
Effective Date: 12/16/2003

A. Construction

Diameters

- 1) Component 1 4 X 1 COND
a) Conductor 24 (7/32) AWG TC
b) Insulation 0.010" Wall, Nom. PVC, Semi Rigid 0.044
(1) Color Code Alpha Wire Color Code E

Cond	Color	Cond	Color	Cond	Color
1	BLACK	3	RED		
2	BROWN	4	ORANGE		

- 2) Cable Assembly 4 Components Bunch Cabled
a) Twists: 8.0 Twists/foot (min)
b) Core Wrap Clear Mylar Tape, 25% Overlap, Min.
3) Jacket 0.032" Wall, Nom., PVC 0.173+/- 0.011
a) Color(s) Gray, Black
b) Ripcord 1 End 810 Denier Nylon
c) Print ALPHA WIRE-* P/N 5014C 4/C 24 AWG
XTRA GUARD 1 75C (UL) TYPE CM OR AWM 2464 ---
LLXXXXXX CSA TYPE CMG FT4 CE
* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- 1) UL
a) Component 1 AWM/STYLE10002 105°C / 300V
b) Overall AWM/STYLE2464 80°C / 300V
CM 75°C / 300V
VW-1
2) CSA International CMG 60°C
FT4
3) CE LVD 73/23/EEC Amendment 93/68/EEC

C. Physical & Mechanical Properties

- 1) Temperature Range -20 to 80°C
2) Bend Radius 10X Cable Diameter

D. Electrical Properties

- 1) Voltage Rating 300 V_{RMS}

E. Other

- 1) Packaging
a) 1000 FT
b) 500 FT
c) 328 FT
d) 100 FT
e) Bulk(Made-to-order)