

Distributed by:

JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 568878

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 5176C
Page 1 of 1 Pages

Issue: 4
Issue Date: 11/5/2003
Effective Date: 12/16/2003

A. Construction

Diameters

- 1) Component 1 6 X 1 COND
a) Conductor 16 (19/.0117) AWG TC
b) Insulation 0.016" Wall, Nom. PVC 0.091
(1) Color Code Alpha Wire Color Code D

Cond	Color	Cond	Color	Cond	Color
1	BLACK	3	WHITE	5	ORANGE
2	RED	4	GREEN	6	BLUE

- 2) Cable Assembly 6 Components Bunch Cabled
a) Twists: 3.0 Twists/foot (min)
b) Core Wrap Clear Mylar Tape, 25% Overlap, Min.
3) Shield: A/P/A Tape, 25% Overlap, Min.
a) Drain Wire 16 (19/.0117) AWG TC
b) Braid TC, 70% Coverage, Min.
4) Jacket 0.032" Wall, Nom., PVC 0.369+/- 0.014
a) Color(s) Gray, Black
b) Ripcord 1 End 810 Denier Nylon
c) Print ALPHA WIRE-* P/N 5176C 6/C 16 AWG
XTRA GUARD 1 SHIELDED 75C (UL) TYPE CM OR AWM 2464
--- LLXXXXXX CSA TYPE CMG FT4 CE
* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- 1) UL
a) Component 1 AWM/STYLE1569 105°C / 300V
b) Overall AWM/STYLE2464 80°C / 300V
CM 75°C / 300V
VW-1
2) CSA International CMG 60°C
FT4
3) CE LVD 73/23/EEC Amendment 93/68/EEC

C. Physical & Mechanical Properties

- 1) Temperature Range -20 to 80°C
2) Bend Radius 10X Cable Diameter

D. Electrical Properties

- 1) Voltage Rating 300 V_{RMS}

E. Other

- 1) Packaging
a) 1000 FT
b) 500 FT
c) 100 FT
d) Bulk(Made-to-order)