


	10	9	8		7	6	5	4	3	2	19072	
	MATERIAL NUMBER	ENGINEERING NUMBER	MILITARY NUMBER	STUD SIZE	"S" ±.005/±0.13	STOCK THICKNESS REF	"W" ±.010/0.25	"C" MIN	"L" MAX	"ID" MIN		
F	190720006	AA-420-02	---	02	.094/2.39	.028/0.71	.225/5.72	.157/3.99	.657/16.69	.062/1.57		F
	190720008	AA-420-04	MS-20659-138	04	.119/3.02							
	190720010	AA-420-06	MS-20659-101	06	.146/3.71							
	190720012	AA-421-06	---									
	190720014	AA-421-08	---	08	.173/4.39		.312/7.93	.270/6.86	.814/20.68	.062/1.57		
190720016	AA-421-10	MS-20659-102	10	.198/5.03								
E	190720018	AA-421-209	---	209	.209/5.30	.031/0.79	.534/13.56	.552/14.02	1.207/30.60	.054/1.37		E
	190720025	AA-426-10	---	10	.198/5.03							
	190720026	AA-426-14	---	14	.265/6.73							
	190720030	AA-426-56	MS-20659-161	56	.328/8.33							
	190720028	AA-426-38	MS-20659-125	38	.390/9.91							



NOTES:
1. MATERIAL: TERMINAL: COPPER
FUNNEL FERRULE: BRASS
PLATING: ELECTRO TIN.

2. MWID = MAXIMUM WIRE INSULATION.

SALES DRAWING

WAS A PART OF AA-CD-401-01 EC NO: ETC2005-0035 DRWN: BENDERLE 2004/08/24 CHKD: R DEROSS 2004/08/24 APPR: RDEROSS 2004/08/24	QUALITY SYMBOLS DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SCALE NONE DESIGN UNITS INCH DIMENSION STYLE IN/MM DRAWN BY BENDERLE DATE 2004/08/18 CHECKED BY R DEROSS DATE 2004/08/18 APPROVED BY R DEROSS DATE 2004/08/18	THIRD ANGLE PROJECTION REVISE ON CAD ONLY TITLE RING TONGUE TERMINAL VIBRAKRIMP 22-18 AWG MOLEX MATERIAL NO. SEE CHART DOCUMENT NO. SD-19072-001 SHEET NO. 1 OF 1