

Distributed by:

JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 800972

FEATURES AND SPECIFICATIONS

Features and Benefits

- Intermateable, intermountable and interchangeable with industry-standard versions
- Cross tested to assure industry compatibility
- Positive locks
- Fully isolated contacts
- Circuit ID grooves to reduce assembly errors
- Anti-stress positioning tabs to reduce breakage

Reference Information

Product Specification: PS-42022-0001

Packaging: Bag

UL File No.: E29179

CSA File No.: LR19980

Designed In: Inches

Electrical

Voltage: 600V

Current:

Circuit	1	2	3	4	6	9	12	15
Amperes	13.5	13.5	13.5	13.5	11.0	11.0	11.0	11.0

Dielectric Withstanding Voltage: 2900V (Header),
5000V (Wire-To-Wire)

Insulation Resistance: 1000 MΩ min.

Mechanical

Contact Retention to Housing: 66.88N (15 lb)

Physical


Cap Housing: Nylon, 94V-2 or 94V-0

Operating Temperature: -55 to +105°C




2.13mm (.084") Diameter MLX Pin and Socket Receptacle

42022



CATALOG DRAWING (FOR REFERENCE ONLY)




ORDERING INFORMATION AND DIMENSIONS


Circuits	Order No.			Dimension								
	94V-2 (White)	94V-0 (Brick Red)	94V-0 (White)	A	B	C	D	E	F	G	H	J
1	50-84-2010	50-84-2011	50-84-2012	9.65 (.380)		9.65 (.380)						
2	• 50-84-2020	• 50-84-2021	50-84-2022	7.62 (.300)		13.97 (.550)	6.35 (.250)	14.35 (.565)	13.46 (.530)	6.35 (.250)	8.64 (.340)	2.41 (.095)
3	• 50-84-2030	• 50-84-2031	50-84-2032	7.62 (.300)		20.32 (.800)	12.70 (.500)	20.70 (.815)	13.46 (.530)	6.35 (.250)	8.64 (.340)	2.41 (.095)
4	• 50-84-2040	• 50-84-2041	50-84-2042	7.62 (.300)		26.67 (1.050)	19.05 (.750)	27.05 (1.065)	13.46 (.530)	6.35 (.250)	8.64 (.340)	2.41 (.095)
6	• 50-84-2060	• 50-84-2061	50-84-2062	20.32 (.800)	12.70 (.500)	13.97 (.550)	6.35 (.250)	14.35 (.565)	26.16 (1.030)	6.35 (.250)	12.19 (.480)	6.99 (.275)
9	• 50-84-2090	• 50-84-2091	50-84-2092	20.32 (.800)	12.70 (.500)	20.32 (.800)	12.70 (.500)	20.70 (.815)	26.16 (1.030)	6.35 (.250)	12.19 (.480)	6.99 (.275)
12	50-84-2120	50-84-2121	50-84-2122	20.32 (.800)	12.70 (.500)	26.67 (1.050)	19.05 (.750)	27.05 (1.065)	26.16 (1.030)	8.89 (.350)	12.19 (.480)	6.99 (.275)
15	50-84-2150	50-84-2151	50-84-2152	20.32 (.800)	12.70 (.500)	33.02 (1.300)	25.40 (1.000)	33.40 (1.315)	26.16 (1.030)	8.89 (.350)	12.19 (.480)	6.99 (.275)

• US Standard Product, available through Molex franchised distributors

* Cap housing should be installed into panel in the same direction as the panel cutout is punched



TERMINAL TEMPERATURE VERSUS CURRENT
FOR BRASS TERMINALS IN FOUR CIRCUIT HOUSINGS



TERMINAL TEMPERATURE VERSUS CURRENT
FOR BRASS TERMINALS IN NINE CIRCUIT HOUSINGS



MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

PRODUCT SPECIFICATION FOR .084/(2.13) DIAMETER SERIES CONNECTOR HOUSINGS AND TERMINALS

(GOLD PLATED TERMINALS ONLY)

1.0 Scope:

This specification covers the .250 inch (6.35mm) centerline gold plated connector series terminated to 14 to 20 AWG wire using crimp technology.

2.0 Product Description:

2.1 Product Name and Part Number

Product Name	Part Number
Housing, Plug, 1 circuit	42021-1*
Housing, Plug, 2 circuit	42021-2*
Housing, Plug, 3 circuit	42021-3*
Housing, Plug, 4 circuit	42021-4*
Housing, Plug, 6 circuit	42021-6*
Housing, Plug, 9 circuit	42021-9*
Housing, Plug, 12 circuit	42021-12*
Housing, Plug, 15 circuit	42021-15*
Housing, cap , 1 circuit	42022-1*
Housing, cap , 2 circuit	42022-2*
Housing, cap , 3 circuit	42022-3*
Housing, cap , 4 circuit	42022-4*
Housing, cap , 6 circuit	42022-6*
Housing, cap , 9 circuit	42022-9*
Housing, cap , 12 circuit	42022-12*
Housing, cap , 15 circuit	42022-15*
Terminal, pin, gold plated	42023-2*2*
Terminal, socket, gold plated	42024-1*2*

2.2 Materials, Platings and Markings

See the appropriate Sales Drawings for information on materials, platings and markings

3.0 Applicable Documents and Specifications:

See the Sales Drawings and the other sections of this Specification.

3.1 Agency approvals:

UL file number: E29179

CSA file number: LR19980

REV.	1	1	1	1	1	1
SHT.	1	2	3	4	5	6

FILE NAME
PS42022X2

▽ = 0

▼ = 0

REVISE ONLY ON CAD SYSTEM

REV. 1

S01

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO
MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT. 1 OF 6

DRWG. NO.
PSX-42022-0002

DRWG. NO.
PSX-42022-0002




MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.


PRODUCT SPECIFICATION FOR .084/(2.13) DIAMETER SERIES CONNECTOR HOUSINGS AND TERMINALS

THESE GRAPHS SHOW TYPICAL (AVERAGE) PERFORMANCE

(GOLD PLATED TERMINALS ONLY)



TEMPERATURE VERSUS CURRENT
FOR BRASS TERMINALS IN FOUR CIRCUIT HOUSINGS
ALL FOUR CIRCUITS CARRY THE INDICATED CURRENT
(VALUES ABOVE THE 30°C RISE ARE EXTRAPOLATED)



TEMPERATURE VERSUS CURRENT
FOR BRASS TERMINALS IN NINE CIRCUIT HOUSINGS
ALL NINE CIRCUITS CARRY THE INDICATED CURRENT
(VALUES ABOVE THE 30°C RISE ARE EXTRAPOLATED)

DRWG. NO.
PSX-42022-0002

REV.

SHT.

FILE NAME
PS42022X2

▽ = 0

▼ = 0

REVISE ONLY ON CAD SYSTEM

REV.

1

S02

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO
MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT.

2

DRWG. NO.
PSX-42022-0002



MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

PRODUCT SPECIFICATION FOR .084/(2.13) DIAMETER SERIES CONNECTOR HOUSINGS AND TERMINALS

(GOLD PLATED TERMINALS ONLY)

4.0 Ratings:

4.1 Voltage: 600 Volts

4.2 Current and Applicable Wires:

ITEM	TEST CONDITION	REQUIREMENT
Temperature Rise	Mate the connectors and measure the contact temperature at the rated current load (IEC STD. 512-3)	Maximum Temperature of the terminal over ambient of 30 C (see sheet 2)

-See sheet 2 for typical temperature versus current curves
-14 to 20 AWG wire - Outside Insulation Diameter .130 inch (3.30mm) Maximum

4.3 Temperature: Operating - 55 C to + 105 C

5.0 Performance Specifications

5.1 Electrical Performance

ITEM	TEST CONDITION	REQUIREMENT
Contact Resistance [Low Level]	Mate connectors with a maximum voltage of 20 mV and a current of 100 mA (MIL-STD-1344A METHOD 3004.1)	3.5 milliohms Maximum (initial)
Insulation Resistance	Mate connectors with a voltage of 500 VDC between adjacent terminals. (MIL-STD-1344A METHOD 3003.1)	1000 Megohms Minimum (initial)
Dielectric Strength	Mate connectors with a voltage of 5000 VAC for 1 minute between adjacent terminals. (MIL-STD-1344A METHOD 3001.1)	No Breakdown

DRWG. NO.
PSX-42022-0002

REV.

SHT.

FILE NAME
PS42022X2

▽ = 0

▼ = 0

REVISE ONLY ON CAD SYSTEM

REV.

1

S03

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO
MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT.

3

DRWG. NO.
PSX-42022-0002



MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

PRODUCT SPECIFICATION FOR .084/(2.13) DIAMETER SERIES CONNECTOR HOUSINGS AND TERMINALS

(GOLD PLATED TERMINALS ONLY)

5.2 Mechanical Performance

ITEM	TEST CONDITION	REQUIREMENT	
		MAX	Min
Connector Insertion and Withdrawal	Insert and withdraw connectors at a rate of 0.5 inches per minute (12.7 mm per minute) (MIL-STD-1344A METHOD 2013.1)	INSERTION 1.5	WITHDRAWAL 0.5
		(per terminal, initial)	
Retention Force in Housing	Axial pull out force on the terminal in the housing at a rate of .5 inches per minute (12.7 mm per minute) (MIL-STD-1344A METHOD 2012.1)	15 lbf	Minimum
Durability	Mate connectors up to 50 cycles at a maximum rate of 5 cycles per minute (MIL-STD-1344A METHOD 2016)	3.6 milliohm	Max
Vibration	Amplitude: .060" (1.5 mm) peak to peak Sweep: 10-55-10 Hertz in one minute Duration: 2 hours in each X-Y-Z axis (MIL-STD-1344A METHOD 2005.1) (TEST CONDITION I)	Appearance: No Damage Contact Resistance: 5.0 milliohm Maximum Discontinuity: 1 micro second Maximum	
Mechanical Shock	50 G's with three shocks in each X-Y-Z axis (MIL-STD-1344A METHOD 2004.1) (TEST CONDITION A)	Appearance: No Damage Contact Resistance: 6 milliohm Maximum Discontinuity: 1 micro second Maximum	
Wire Pullout Force (Axial)	Apply an axial pullout force on the wire at a rate of 1 +/- 1/4 inch per minute (25 +/- 6 mm per minute) (MIL-STD-1344A METHOD 2003.1)	AWG	Pullout Force
		14	50 lbf
		16	45 lbf
		18	30 lbf
		20	14 lbf
Terminal Insertion Force (Axial)	Apply an axial insertion force on the terminal at a rate of 1 +/- 1/4 inch per minute (25 +/- 6 mm per minute) (MIL-STD-1344A METHOD 2012.1)	2.0 lbf	Maximum

DRWG. NO.
PSX-42022-0002

REV.

SHT.

FILE NAME
PS42022X2

▽ = 0

▼ = 0

REVISE ONLY ON CAD SYSTEM

REV.

I

S04

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT.

4

DRWG. NO.
PSX-42022-0002



MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

PRODUCT SPECIFICATION FOR .084/(2.13) DIAMETER SERIES CONNECTOR HOUSINGS AND TERMINALS

(GOLD PLATED TERMINALS ONLY)

5.2 Mechanical performance (continued):

ITEM	TEST CONDITION	REQUIREMENT
Plug latch strength	Mate connectors and pull apart until both latches break, record the maximum force.	Minimum 35.0 lbf
Panel retention for cap	Insert cap housing into panel cut out per the sales drawing requirements, push cap opposite the way it was assembled until the locking barbs break, record the maximum force.	Minimum 75.0 lbf

5.3 Environmental Performance

ITEM	TEST CONDITION	REQUIREMENT
Thermal Shock	Mate connectors exposed for 25 cycles of: Temperature Duration -55 +0/-3 C 30 minutes 85 +3/0 C 30 minutes (MIL-STD-1344A METHOD 1003.1) (TEST CONDITION A-1)	Appearance: No Damage Contact Resistance: 3.75 milliohm Maximum Dielectric strength: 5000 Vac for 1 minute
Humidity-temperature cycling	Mate connectors and expose to Temperature -humidity cycling between 25 c and 65 c at 95% RH, -10 c with humidity not controlled (MIL-STD-1344A METHOD 1002.1) (TYPE II)	Appearance: No Damage Contact Resistance: 6.00 milliohm Maximum Dielectric Strength: 5000 VAC for 1 minute Insulation Resistance: 100 Megohms Minimum
Salt spray	Expose unmated connector assemblies to a salt spray concentration of 5% at 35 C for 48 hours. (MIL-STD-1344A METHOD 1001.1)	7.00 milliohm Maximum Dielectric Strength: 5000 VAC for 1 minute

DRWG. NO.
PSX-42022-0002

REV.

SHT.

FILE NAME
PS42022X2

= 0

= 0

REVISE ONLY ON CAD SYSTEM

REV.

1

S05

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO
MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT.

5

DRWG. NO.
PSX-42022-0002



(GOLD PLATED TERMINALS ONLY)

[illegible]

DRWG. NO.
PSX-42022-0002

DRWG. NO.
PSX-42022-00002

REV.				
SHT.				
FILE NAME PS42022X2	 = 0  = 0	REVISE ONLY ON CAD SYSTEM	REV.	I
S06	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		SHT.	6

