

Distributed by:

JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 881400

FEATURES AND SPECIFICATIONS

Features and Benefits

- Positive housing locks to mate with Mini-Fit, Jr. receptacle
- Fully isolated terminals to protect contacts from damage
- Drain hole option available

Reference Information

Product Specification: PS-5556-0001

Packaging: Tray or bag

UL File No.: E29179

CSA File No.: LR19980

TUV License No.: R75142

Mates With: 5557 dual row receptacle

Designed In: Millimeters

Electrical

Voltage: 600V

Current: (Used with 16 AWG)

Circuits	2-3	4-6	7-10	12-24
Amperes-Jr.	9	8	7	6

Electrical (cont'd)

Contact Resistance: 10mΩ max.

Dielectric Withstanding Voltage: 1500V AC

Insulation Resistance: 1000 MΩ min.

Mechanical

Contact Insertion Force: 1.5kg max.

Contact Retention to Housing: 3.0kg min.

Wire Pull-Out Force: 9.0kg min.

Insertion Force to PCB: 5.0kg max.

Mating Force: 0.7kg (1.54 lb) max.

Unmating Force: 0.35kg (0.7 lb) min.

Normal Force: 200g min.

Durability: 30 cycles

Physical

Housing: 6/6 nylon, UL 94V-2 or 94V-0

Contact: Brass or Phosphor Bronze

Plating: Tin, select Gold or overall Gold


Operating Temperature: -40 to +105°C






4.20mm (.165") Pitch Mini-Fit, Jr.™ Header

5566

Vertical, Dual Row Without Pegs



CATALOG DRAWING (FOR REFERENCE ONLY)



PCB LAYOUT: COMPONENT SIDE
RECOMMENDED PCB THICKNESS: $\frac{1.60}{.063}$

ORDERING INFORMATION AND DIMENSIONS

With Drain Holes						
Circuits	Order No.				Dimension	
	Tin Plated		Gold Plated (30μ")		A	B
	94V-2	94V-0	94V-2	94V-0		
2	•39-29-3026	•39-31-0020	•39-31-0027	•39-31-0028	5.40 (.210)	
4	•39-29-3046	•39-31-0040	•39-31-0047	•39-31-0048	9.60 (.380)	4.20 (.170)
6	•39-29-3066	•39-31-0060	•39-31-0067	•39-31-0068	13.80 (.540)	8.40 (.330)
8	•39-29-3086	•39-31-0080	•39-31-0087	•39-31-0088	18.00 (.710)	12.60 (.500)
10	•39-29-3106	•39-31-0100	•39-31-0107	•39-31-0108	22.20 (.870)	16.80 (.660)
12	•39-29-3126	•39-31-0120	•39-31-0127	•39-31-0128	26.40 (1.040)	21.00 (.830)
14	•39-29-3146	•39-31-0140	•39-31-0147	•39-31-0148	30.60 (1.200)	25.20 (.990)
16	•39-29-3166	•39-31-0160	•39-31-0167	•39-31-0168	34.80 (1.370)	29.40 (1.160)
20	•39-29-3206		•39-31-0207		43.20 (1.700)	37.80 (1.490)
22	•39-29-3226		•39-31-0227		47.40 (1.870)	42.00 (1.650)

* US Standard Product, available through Molex franchised distributors

Without Drain Holes						
Circuits	Order No.				Dimension	
	Tin Plated		Gold Plated (30μ")		A	B
	94V-2	94V-0	94V-2	94V-0		
2	•39-28-1023	•39-28-8020	•39-29-0023	•39-29-6028	5.40 (.210)	
4	•39-28-1043	•39-28-8040	•39-29-0043	•39-29-6048	9.60 (.380)	4.20 (.170)
6	•39-28-1063	•39-28-8060	•39-29-0063	•39-29-6068	13.80 (.540)	8.40 (.330)
8	•39-28-1083	•39-28-8080	•39-29-0083	•39-29-6088	18.00 (.710)	12.60 (.500)
10	•39-28-1103	•39-28-8100	•39-29-0103	•39-29-6108	22.20 (.870)	16.80 (.660)
12	•39-28-1123	•39-28-8120	•39-29-0123	•39-29-6128	26.40 (1.040)	21.00 (.830)
14	•39-28-1143	•39-28-8140	•39-29-0143	•39-29-6148	30.60 (1.200)	25.20 (.990)
16	•39-28-1163	•39-28-8160	•39-29-0163	•39-29-6168	34.80 (1.370)	29.40 (1.160)
18	•39-28-1183	•39-28-8180	•39-29-0183	•39-29-6188	39.00 (1.540)	33.60 (1.320)
20	•39-28-1203	•39-28-8200	•39-29-0203	•39-29-6208	43.20 (1.700)	37.80 (1.490)
22	•39-28-1223	•39-28-8220	•39-29-0223	•39-29-6228	47.40 (1.870)	42.00 (1.650)
24	•39-28-1243	•39-28-8240	•39-29-0243	•39-29-6248	51.60 (2.030)	46.20 (1.820)

製品仕様書・PRODUCT SPECIFICATION

【1. 適用範囲 SCOPE】

本仕様書は、_____殿 に納入する

4. 2mmピッチ プリント基板用 コネクタ について規定する。

This specification covers the 4.2mm CENTER SPACING P.C. BOARD CONNECTOR series.

【2. 製品名称及び型番 PRODUCT NAME AND PART NUMBER】

製品名称 Product Name	製品型番 Part Number
ターミナル Terminal (AWG #18~#24)	5 5 5 6 P B T, P B T L
ハウジング Housing (UL 94V-2)	5 5 5 7 - N R
ハウジング Housing (UL 94V-0)	5 5 5 7 - N R - 2 1 0
ヘッダー アッセンブリ (UL 94V-2) Header Assembly	5 5 6 6 - N A
ヘッダー アッセンブリ (UL 94V-0) Header Assembly	5 5 6 6 - N A - 2 1 0

N : 図面参照 Refer to the drawing.

【3. 定格及び適用電線 RATINGS AND APPLICABLE WIRES】

項 目 Item	規 格 Standard		
最大許容電圧 Rated Voltage(MAX.)	6 0 0 V [A C (実効値 rms) / D C]		
最大許容電流 及び適用電線 Rated Current (MAX.) and Applicable wires	A W G # 1 8	5 A	被覆外径 : Insulation O.D. φ 1.3 ~ φ 3.1mm
	A W G # 2 0	4 A	
	A W G # 2 2	3 A	
	A W G # 2 4	2 A	
使用温度範囲 Ambient temperature Range	- 4 0 ° C ~ + 1 0 5 ° C * ¹		

*¹: 通電による温度上昇分も含む。

Including terminal temperature rise.

【 4 . 性 能 PERFORMANCE】

4 - 1 . 電 氣 的 性 能 Electrical Performance

項 目 Item		条 件 Test Condition	規 格 Requirement
4-1-1	接 触 抵 抗 Contact Resistance	コネクタを嵌合させ、開放電圧 20mV 以下、 短絡電流 10mA にて測定する。 (JIS C5402 5.4) Mate connectors, measure by dry circuit, 20mV MAX., 10mA. (JIS C5402 5.4)	10 mΩ MAX.
4-1-2	絶 縁 抵 抗 Insulation Resistance	コネクタを嵌合させ、隣接するターミナル間 及びターミナル、アース間に、DC 500V を 印加し測定する。 (JIS C5402 5.2/MIL-STD-202 試験法 302) Mate connectors, apply 500V DC between adjacent terminal or ground. (JIS C5402 5.2/MIL-STD-202 Method 302)	1000 MΩ MIN.
4-1-3	耐 電 圧 Dielectric Strength	コネクタを嵌合させ、隣接するターミナル間 及びターミナル、アース間に、 AC 1500V (実効値) を 1分間 印加する。 (JIS C5402 5.1/MIL-STD-202 試験法 301) Mate connectors, apply 1500V AC for 1 minute between adjacent terminal or ground. (JIS C5402 5.1/MIL-STD-202 Method 301)	異状なきこと No Breakdown
4-1-4	圧着部接触抵抗 Contact Resistance on Crimped Portion	ターミナルに適合電線を圧着し、開放電圧 20mV 以下、短絡電流 10mA にて測定する。 Crimp the applicable wire on to the terminal, measure by dry circuit, 20mV MAX., 10mA.	5 mΩ MAX.

4-2. 機械的性能 Mechanical Performance

項 目 Item		条 件 Test Condition		規 格 Requirement
4-2-1	挿入力及び抜去力 Insertion and Withdrawal Force	毎分 $25 \pm 3\text{mm}$ の速さで挿入、抜去を行なう。 Insert and withdraw connectors at the speed rate of $25 \pm 3\text{mm/minute}$.		第 6 項 参 照 Refer to paragraph 6
4-2-2	圧着部引張り強度 Crimping Pull Out Force	圧着されたターミナルを治具に固定し、電線を軸方向に毎分 $25 \pm 3\text{mm}$ の速さで引張る。 (JIS C5402 6.8) Fix the crimped terminal, apply axial pull out force on the wire at the speed rate of $25 \pm 3\text{mm/minute}$. (JIS C5402 6.8)	AWG.#18	88.2 N {9.0 kgf} MIN.
			AWG.#20	58.8 N {6.0 kgf} MIN.
			AWG.#22	39.2 N {4.0 kgf} MIN.
			AWG.#24	29.4 N {3.0 kgf} MIN.
4-2-3	ターミナル挿入力 Terminal Insertion Force	圧着されたターミナルをハウジングに挿入する。 Insert the crimped terminal into the housing.		14.7 N {1.5 kgf} MAX.
4-2-4	ターミナル保持力 Terminal/ Housing Retention Force	圧着されたターミナルをハウジングに装着し、電線を軸方向に毎分 $25 \pm 3\text{mm}$ の速さで引張る。 Apply axial pull out force at the speed rate of $25 \pm 3\text{mm/minute}$ on the terminal assembled in the housing.		29.4 N {3.0 kgf} MIN.
4-2-5	ピン保持力 Pin Retention Force	毎分 $25 \pm 3\text{mm}$ の速さでピンを軸方向に押す。 Apply axial push force at the speed rate of $25 \pm 3\text{mm/minute}$.		9.8 N {1.0 kgf} MIN.

4-3. その他 Environmental Performance and Others

項 目 Item		条 件 Test Condition	規 格 Requirement	
4-3-1	繰返し挿抜 Repeated Insertion/ Withdrawal	1分間 10回 以下の速さで挿入、 抜去を 30回 繰返す。 When mated up to 30 cycles repeatedly by the rate of 10 cycles per minute.	接触抵抗 Contact Resis- tance	20 mΩ MAX.
4-3-2	温 度 上 昇 Temperature Rise	コネクタを嵌合させ、最大許容電流 を通電し、コネクタの温度上昇分を 測定する。(UL 498) Carrying rated current load. (UL 498)	温度上昇 Tempera- ture rise	30 °C MAX.
4-3-3	耐 振 動 性 Vibration	DC 1mA 通電状態にて、嵌合軸を含 む互いに垂直な 3方向 に掃引割合 10~55~10 Hz/分 全振幅 1.5mm の振動を 各2時間 加える。 (MIL-STD-202 試験法 201) Amplitude: 1.5mm P-P Sweep time: 10-55-10 Hz in 1 minute Duration: 2 hours in each X.Y.Z. axes (MIL-STD-202 Method 201)	外 観 Appearance	異状なきこと No Damage
			接触抵抗 Contact Resistance	20 mΩ MAX.
			瞬 断 Dis- continuity	1 μsec. MAX.
4-3-4	耐 衝 撃 性 Shock	DC 1mA 通電状態にて、嵌合軸を含 む互いに垂直な 6方向 に 490m/S ² {50G} の衝撃を 各3回 加える。 (JIS C0041/MIL-STD-202 試験法 213) 490m/S ² {50G} , 3 strokes in each X.Y.Z. axes. (JIS C0041 MIL-STD-202 Method 213)	外 観 Appearance	異状なきこと No Damage
			接触抵抗 Contact Resistance	20 mΩ MAX.
			瞬 断 Dis- continuity	1 μsec. MAX.
4-3-5	耐 熱 性 Heat Resistance	コネクタを嵌合させ、105±2°C の 雰囲気中に 96時間 放置後取り出 し、1~2時間 室温に放置する。 (JIS C0021/MIL-STD-202 試験法 108) 105±2°C, 96 hours (JIS C0021/MIL-STD-202 Method 108)	外 観 Appearance	異状なきこと No Damage
			接触抵抗 Contact Resistance	20 mΩ MAX.
4-3-6	耐 寒 性 Cold Resistance	コネクタを嵌合させ、-40±3°C の 雰囲気中に 96時間 放置後取り出 し、1~2時間 室温に放置する。 (JIS C0020) -40±3°C, 96 hours (JIS C0020)	外 観 Appearance	異状なきこと No Damage
			接触抵抗 Contact Resistance	20 mΩ MAX.

項 目 Item		条 件 Test Condition	規 格 Requirement	
4-3-7	耐 湿 性 Humidity	コネクタを嵌合させ、 $60\pm 2^{\circ}\text{C}$ 、 相対湿度 90~95% の雰囲気中に 96時間 放置後取り出し、1~2時間 室温に放置する。 (JIS C0022/MIL-STD-202 試験法 103) Temperature: $60\pm 2^{\circ}\text{C}$ Relative Humidity: 90~95% Duration: 96 hours (JIS C0022/MIL-STD-202 Method 103)	外 観 Appearance	異状なきこと No Damage
			接触抵抗 Contact Resistance	20 m Ω MAX.
			耐 電 圧 Dielectric Strength	4-1-3項満足のこと Must meet 4-1-3
			絶縁抵抗 Insulation Resistance	100 M Ω MIN.
4-3-8	温 度 サ イ ク ル Temperature Cycling	コネクタを嵌合させ、 -55°C に 30分、 $+105^{\circ}\text{C}$ に 30分 これを 1 サイクル とし、5サイクル 繰返す。 但し、温度移行時間は 5分 以内と する。試験後 1~2時間 室温に 放置する。(JIS C0025) 5 cycles of: a) -55°C 30 minutes b) $+105^{\circ}\text{C}$ 30 minutes (JIS C0025)	外 観 Appearance	異状なきこと No Damage
			接触抵抗 Contact Resistance	20 m Ω MAX.
4-3-9	塩 水 噴 霧 Salt Spray	コネクタを嵌合させ、 $35\pm 2^{\circ}\text{C}$ にて $5\pm 1\%$ 重量比の塩水を 48 ± 4 時間 噴霧し、試験後常温で水洗いした 後、室温で乾燥させる。 (JIS C0023/MIL-STD-202 試験法 101) 48 ± 4 hours exposure to a salt spray from the $5\pm 1\%$ solution at $35\pm 2^{\circ}\text{C}$. (JIS C0023/MIL-STD- 202 Method 101)	外 観 Appearance	異状なきこと No Damage
			接触抵抗 Contact Resistance	20 m Ω MAX.
4-3-10	亜 硫 酸 ガ ス SO_2 Gas	コネクタを嵌合させ、 $40\pm 2^{\circ}\text{C}$ にて $50\pm 5\text{ppm}$ の亜硫酸ガス中に 24時間 放置する。 24 hours exposure to $50\pm 5\text{ppm}$. SO_2 gas at $40\pm 2^{\circ}\text{C}$.	外 観 Appearance	異状なきこと No Damage
			接触抵抗 Contact Resistance	20 m Ω MAX.
4-3-11	半 田 付 け 性 Solder- ability	ターミナルまたはピンをフラックス に浸し、本体の取付け基準面より 1.2mm 迄、 $230\pm 5^{\circ}\text{C}$ の半田に 3 ± 0.5 秒 浸す。 Soldering Time: 3 ± 0.5 sec. Solder Temperature: $230\pm 5^{\circ}\text{C}$	濡 れ 性 Solder Wetting	浸漬面積の 75%以上 75% of immersed area must show no voids, pin holes

項 目 Item		条 件 Test Condition	規 格 Requirement	
4-3-12	半 田 耐 熱 性 Resistance to Solder- ing Heat	ターミナルまたはピンを本体の取付け 基準面より 1.2mm 迄、 $260\pm 5^{\circ}\text{C}$ の半 田に 5 ± 0.5 秒 浸す。 Solder Temperature: $260\pm 5^{\circ}\text{C}$ Soldering Time: 5 ± 0.5 sec.	外 観 Appearance	端子ガタ、 割れ等 異状なきこと No Damage

() : 参考規格
Reference Standard

【 5 . 外 観 形 状、寸 法 及 び 材 質 PRODUCT SHAPE, DIMENSIONS AND MATERIALS】

図面参照 Refer to the drawing.

【 6 . 挿入力及び抜去力 INSERTION/WITHDRAWAL FORCE】

極 数 No. of CKT	単位 UNIT	挿入力 (最大値) Insertion (MAX.)			抜去力 (最小値) Withdrawal (MIN.)		
		初 回 1st	6 回目 6th	30回目 30th	初 回 1st	6 回目 6th	30回目 30th
2	N kgf	13.8 {1.4}	12.8 {1.3}	12.8 {1.3}	0.98 {0.10}	0.78 {0.08}	0.78 {0.08}
4	N kgf	27.5 {2.8}	25.5 {2.6}	25.5 {2.6}	1.96 {0.20}	1.56 {0.16}	1.56 {0.16}
6	N kgf	41.2 {4.2}	38.3 {3.9}	38.3 {3.9}	2.94 {0.30}	2.35 {0.24}	2.35 {0.24}
8	N kgf	54.9 {5.6}	51.0 {5.2}	51.0 {5.2}	3.92 {0.40}	3.13 {0.32}	3.13 {0.32}
1 0	N kgf	68.6 {7.0}	63.7 {6.5}	63.7 {6.5}	4.90 {0.50}	3.92 {0.40}	3.92 {0.40}
1 2	N kgf	82.4 {8.4}	76.5 {7.8}	76.5 {7.8}	5.88 {0.60}	4.70 {0.48}	4.70 {0.48}
1 4	N kgf	96.1 {9.8}	89.2 {9.1}	89.2 {9.1}	6.86 {0.70}	5.48 {0.56}	5.48 {0.56}
1 6	N kgf	109.8 {11.2}	102.0 {10.4}	102.0 {10.4}	7.84 {0.80}	6.27 {0.64}	6.27 {0.64}
1 8	N kgf	123.5 {12.6}	114.7 {11.7}	114.7 {11.7}	8.82 {0.90}	7.05 {0.72}	7.05 {0.72}
2 0	N kgf	137.2 {14.0}	127.4 {13.0}	127.4 {13.0}	9.80 {1.00}	7.84 {0.80}	7.84 {0.80}
2 2	N kgf	151.0 {15.4}	140.2 {14.3}	140.2 {14.3}	10.78 {1.10}	8.62 {0.88}	8.62 {0.88}
2 4	N kgf	164.7 {16.8}	152.9 {15.6}	152.9 {15.6}	11.76 {1.20}	9.40 {0.96}	9.40 {0.96}




Figure 1 illustrates various 2D array structures, each labeled with the number of CXTs (Crossbar eXtended Transistors) it contains. The structures are arranged in three rows:

- Row 1: 6 CXTs, 8 CXTs, 18 CXTs, 20 CXTs.
- Row 2: 4 CXTs, 10 CXTs, 16 CXTs, 22 CXTs.
- Row 3: 2 CXTs, 12 CXTs, 14 CXTs, 24 CXTs.

Each structure is represented by a grid of boxes, where each box contains a number indicating the CXTs used in that configuration. The boxes are arranged in rows and columns, with some boxes containing multiple numbers, indicating that a single CXT can be used in multiple configurations.

CIRCUIT SIZE LAYOUT
(SCALE 1:1)

NOTES

1. MATE WITH : 5557 SERIES
2. LEGEND

```

BASE NUMBER _____
CIRCUIT SIZE _____
ASS'Y TYPE _____
    A : WITHOUT DRAIN HOLES
    B : WITH DRAIN HOLES
TERMINAL MATERIAL _____
"BLANK" : BRASS
    PB : PHOSPHOR BRONZE
TERMINAL PLATING _____
"BLANK": BRIGHT TIN 0.9µm MIN.OVER COPPER 0.5µm MIN.(BRASS)
        TIN 0.9µm MIN. REFLOW TREATMENT
        OR BRIGHT TIN 0.9µm MIN.(PHOSPHOR BRONZE)
    S : BRIGHT TIN 2.54µm MIN.OVER NICKEL 1.27µm MIN.
    GS : SELECT GOLD 0.76µm MIN.AND SELECT PURE TIN 2.54µm MIN.
        OVER NICKEL 1.27µm MIN.
    GS2 : SELECT GOLD 0.38µm MIN.AND SELECT PURE TIN 2.54µm MIN.
        OVER NICKEL 1.27µm MIN.
HOUSING MATERIAL _____
"BLANK" : NYLON 66, UL94V-2
    210 : NYLON 66, UL94V-0
    310 : G.F. 30% PCT, UL94V-0
    400 : NYLON 66, UL94V-0, BLACK
COLOR _____

```

BL : BLACK RE : RED GR : GRAY
BU : BLUE YE : YELLOW 5566-N***-x->

3	EXTERNAL RIB APPEARS ON MX-USA PARTS ONLY.	MODEL NO.
---	--	-----------

REVISED	EC NO: J2005-3557	2005/06/06 DOWN:HABEI	2005/06/07 CHKD:KTOJO	2005/06/10 APPR:NUKITA	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC		THIRD ANGLE PROJECTION
						10 UNDER	± 0.2	DRAWN BY H. HIRAMOTO	DATE '89/04/03	TITLE NEW MINI FIT CONNECTOR HEADER HOUSING ASS'Y -LEAD FREE-			
						10 OVER 30 UNDER	± 0.3	CHECKED BY M. FUKUSHIMA	DATE '94/04/20				
						30 OVER	± 0.4	APPROVED BY M. FUKUSHIMA	DATE '94/04/20				
						ANGULAR ±3 °		MATERIAL NO.					
						REV	K	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				SEE CHART	
				SIZE A3				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					

	10	9	8	7	6	5	4	3	2	1	
F	NOT TOOLED	5566-24APB-3 IO	NOT TOOLED	5566-24AGS2-3 IO	NOT TOOLED	5566-24AGS-3 IO	NOT TOOLED	5566-24AS-3 IO	NOT TOOLED	5566-24A-3 IO	24
	↑	↑ -22APB-3 IO	↑	↑ -22AGS2-3 IO	↑	↑ -22AGS-3 IO	↑	↑ -22AS-3 IO	↑	↑ -22A-3 IO	22
		-20APB-3 IO		-20AGS2-3 IO		-20AGS-3 IO		-20AS-3 IO		-20A-3 IO	20
		-18APB-3 IO		-18AGS2-3 IO		-18AGS-3 IO		-18AS-3 IO		-18A-3 IO	18
		-16APB-3 IO		-16AGS2-3 IO		-16AGS-3 IO		-16AS-3 IO		-16A-3 IO	16
		-14APB-3 IO		-14AGS2-3 IO		-14AGS-3 IO		-14AS-3 IO		-14A-3 IO	14
		-12APB-3 IO		-12AGS2-3 IO		-12AGS-3 IO		-12AS-3 IO		-12A-3 IO	12
		-10APB-3 IO		-10AGS2-3 IO		-10AGS-3 IO		-10AS-3 IO		-10A-3 IO	10
		-08APB-3 IO		-08AGS2-3 IO		-08AGS-3 IO		-08AS-3 IO		-08A-3 IO	8
		-06APB-3 IO		-06AGS2-3 IO		-06AGS-3 IO		-06AS-3 IO		-06A-3 IO	6
↓	↓ -04APB-3 IO	↓	↓ -04AGS2-3 IO	↓	↓ -04AGS-3 IO	↓	↓ -04AS-3 IO	↓	↓ -04A-3 IO	4	
NOT TOOLED	5566-02APB-3 IO	NOT TOOLED	5566-02AGS2-3 IO	NOT TOOLED	5566-02AGS-3 IO	NOT TOOLED	5566-02AS-3 IO	NOT TOOLED	5566-02A-3 IO	2	
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	CKT. SIZE	
5566-NAPB-3 IO		5566-NAGS2-3 IO		5566-NAGS-3 IO		5566-NAS-3 IO		5566-NA-3 IO			
39-29-5247	5566-24APB-2 IO	39-30-9245	5566-24AGS2-2 IO	39-29-6248	5566-24AGS-2 IO	39-30-6242	5566-24AS-2 IO	39-28-8240	5566-24A-2 IO	24	
↑ -5227	↑ -22APB-2 IO	↑ -9225	↑ -22AGS2-2 IO	↑ -6228	↑ -22AGS-2 IO	↑ -6222	↑ -22AS-2 IO	↑ -8220	↑ -22A-2 IO	22	
-5207	-20APB-2 IO	-9205	-20AGS2-2 IO	-6208	-20AGS-2 IO	-6202	-20AS-2 IO	-8200	-20A-2 IO	20	
-5187	-18APB-2 IO	-9185	-18AGS2-2 IO	-6188	-18AGS-2 IO	-6182	-18AS-2 IO	-8180	-18A-2 IO	18	
-5167	-16APB-2 IO	-9165	-16AGS2-2 IO	-6168	-16AGS-2 IO	-6162	-16AS-2 IO	-8160	-16A-2 IO	16	
-5147	-14APB-2 IO	-9145	-14AGS2-2 IO	-6148	-14AGS-2 IO	-6142	-14AS-2 IO	-8140	-14A-2 IO	14	
-5127	-12APB-2 IO	-9125	-12AGS2-2 IO	-6128	-12AGS-2 IO	-6122	-12AS-2 IO	-8120	-12A-2 IO	12	
-5107	-10APB-2 IO	-9105	-10AGS2-2 IO	-6108	-10AGS-2 IO	-6102	-10AS-2 IO	-8100	-10A-2 IO	10	
-5087	-08APB-2 IO	-9085	-08AGS2-2 IO	-6088	-08AGS-2 IO	-6082	-08AS-2 IO	-8080	-08A-2 IO	8	
-5067	-06APB-2 IO	-9065	-06AGS2-2 IO	-6068	-06AGS-2 IO	-6062	-06AS-2 IO	-8060	-06A-2 IO	6	
↓ -5047	↓ -04APB-2 IO	↓ -9045	↓ -04AGS2-2 IO	↓ -6048	↓ -04AGS-2 IO	↓ -6042	↓ -04AS-2 IO	↓ -8040	↓ -04A-2 IO	4	
39-29-5027	5566-02APB-2 IO	39-30-9025	5566-02AGS2-2 IO	39-29-6028	5566-02AGS-2 IO	39-30-6022	5566-02AS-2 IO	39-28-8020	5566-02A-2 IO	2	
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	CKT. SIZE	
5566-NAPB-2 IO		5566-NAGS2-2 IO		5566-NAGS-2 IO		5566-NAS-2 IO		5566-NA-2 IO			
39-29-5246	5566-24APB	39-30-9244	5566-24AGS2	39-29-0243	5566-24AGS	39-30-6241	5566-24AS	39-28-1243	5566-24A	24	
↑ -5226	↑ -22APB	↑ -9224	↑ -22AGS2	↑ -0223	↑ -22AGS	↑ -6221	↑ -22AS	↑ -1223	↑ -22A	22	
-5206	-20APB	-9204	-20AGS2	-0203	-20AGS	-6201	-20AS	-1203	-20A	20	
-5186	-18APB	-9184	-18AGS2	-0183	-18AGS	-6181	-18AS	-1183	-18A	18	
-5166	-16APB	-9164	-16AGS2	-0163	-16AGS	-6161	-16AS	-1163	-16A	16	
-5146	-14APB	-9144	-14AGS2	-0143	-14AGS	-6141	-14AS	-1143	-14A	14	
-5126	-12APB	-9124	-12AGS2	-0123	-12AGS	-6121	-12AS	-1123	-12A	12	
-5106	-10APB	-9104	-10AGS2	-0103	-10AGS	-6101	-10AS	-1103	-10A	10	
-5086	-08APB	-9084	-08AGS2	-0083	-08AGS	-6081	-08AS	-1083	-08A	8	
-5066	-06APB	-9064	-06AGS2	-0063	-06AGS	-6061	-06AS	-1063	-06A	6	
↓ -5046	↓ -04APB	↓ -9044	↓ -04AGS2	↓ -0043	↓ -04AGS	↓ -6041	↓ -04AS	↓ -1043	↓ -04A	4	
39-29-5026	5566-02APB	39-30-9024	5566-02AGS2	39-29-0023	5566-02AGS	39-30-6021	5566-02AS	39-28-1023	5566-02A	2	
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	CKT. SIZE	
5566-NAPB		5566-NAGS2		5566-NAGS		5566-NAS		5566-NA			

REVISED EC NO.: J2005-3557 DRAWN: NABEI CHKD: K10 JO APPR: NUKI TA K	DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
		10 UNDER	± ---	DRAWN BY H. HIRAMOTO	DATE '89/04/03	TITLE NEW MINI FIT CONNECTOR HEADER HOUSING ASS'Y -LEAD FREE- MOLEX MOLEX INCORPORATED		
		10 OVER 30 UNDER	± ---	CHECKED BY M. FUKUSHIMA	DATE '94/04/20			
		30 OVER	± ---	APPROVED BY M. FUKUSHIMA	DATE '94/04/20			
		ANGULAR ± --- °		MATERIAL NO.		DOCUMENT NO. SD-5566-002		SHEET NO. 2 OF 5
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

tb_frame_A3_J_ME_S Rev. D 2004/04/02	9	8	7	6	5	4	3	2	EN-02JA(021)
---	---	---	---	---	---	---	---	---	--------------

	10	9	8	7	6	5	4	3	2	1	
F	NOT TOOLED	5566-24BGS2-3 IO	NOT TOOLED	5566-24BGS-3 IO	NOT TOOLED	5566-24BS-3 IO	NOT TOOLED	5566-24B-3 IO	NOT TOOLED	5566-24APBS-3 IO	24
	↑	↑ -22BGS2-3 IO	↑	↑ -22BGS-3 IO	↑	↑ -22BS-3 IO	↑	↑ -22B-3 IO	↑	↑ -22APBS-3 IO	22
		-20BGS2-3 IO		-20BGS-3 IO		-20BS-3 IO		-20B-3 IO		-20APBS-3 IO	20
		-18BGS2-3 IO		-18BGS-3 IO		-18BS-3 IO		-18B-3 IO		-18APBS-3 IO	18
		-16BGS2-3 IO		-16BGS-3 IO		-16BS-3 IO		-16B-3 IO		-16APBS-3 IO	16
		-14BGS2-3 IO		-14BGS-3 IO		-14BS-3 IO		-14B-3 IO		-14APBS-3 IO	14
		-12BGS2-3 IO		-12BGS-3 IO		-12BS-3 IO		-12B-3 IO		-12APBS-3 IO	12
		-10BGS2-3 IO		-10BGS-3 IO		-10BS-3 IO		-10B-3 IO		-10APBS-3 IO	10
		-08BGS2-3 IO		-08BGS-3 IO		-08BS-3 IO		-08B-3 IO		-08APBS-3 IO	8
		-06BGS2-3 IO		-06BGS-3 IO		-06BS-3 IO		-06B-3 IO		-06APBS-3 IO	6
	↓	↓ -04BGS2-3 IO	↓	↓ -04BGS-3 IO	↓	↓ -04BS-3 IO	↓	↓ -04B-3 IO	↓	↓ -04APBS-3 IO	4
NOT TOOLED	5566-02BGS2-3 IO	NOT TOOLED	5566-02BGS-3 IO	NOT TOOLED	5566-02BS-3 IO	NOT TOOLED	5566-02B-3 IO	NOT TOOLED	5566-02APBS-3 IO	2	
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	CKT. SIZE	
5566-NBGS2-3 IO		5566-NBGS-3 IO		5566-NBS-3 IO		5566-NB-3 IO		5566-NAPBS-3 IO			
39-30-9247	5566-24BGS2-2 IO	39-31-0248	5566-24BGS-2 IO	39-31-0242	5566-24BS-2 IO	39-31-0240	5566-24B-2 IO	39-30-6244	5566-24APBS-2 IO	24	
↑ -9227	↑ -22BGS2-2 IO	↑ -0228	↑ -22BGS-2 IO	↑ -0222	↑ -22BS-2 IO	↑ -0220	↑ -22B-2 IO	↑ -6224	↑ -22APBS-2 IO	22	
-9207	-20BGS2-2 IO	-0208	-20BGS-2 IO	-0202	-20BS-2 IO	-0200	-20B-2 IO	-6204	-20APBS-2 IO	20	
-9187	-18BGS2-2 IO	-0188	-18BGS-2 IO	-0182	-18BS-2 IO	-0180	-18B-2 IO	-6184	-18APBS-2 IO	18	
-9167	-16BGS2-2 IO	-0168	-16BGS-2 IO	-0162	-16BS-2 IO	-0160	-16B-2 IO	-6164	-16APBS-2 IO	16	
-9147	-14BGS2-2 IO	-0148	-14BGS-2 IO	-0142	-14BS-2 IO	-0140	-14B-2 IO	-6144	-14APBS-2 IO	14	
-9127	-12BGS2-2 IO	-0128	-12BGS-2 IO	-0122	-12BS-2 IO	-0120	-12B-2 IO	-6124	-12APBS-2 IO	12	
-9107	-10BGS2-2 IO	-0108	-10BGS-2 IO	-0102	-10BS-2 IO	-0100	-10B-2 IO	-6104	-10APBS-2 IO	10	
-9087	-08BGS2-2 IO	-0088	-08BGS-2 IO	-0082	-08BS-2 IO	-0080	-08B-2 IO	-6084	-08APBS-2 IO	8	
-9067	-06BGS2-2 IO	-0068	-06BGS-2 IO	-0062	-06BS-2 IO	-0060	-06B-2 IO	-6064	-06APBS-2 IO	6	
↓ -9047	↓ -04BGS2-2 IO	↓ -0048	↓ -04BGS-2 IO	↓ -0042	↓ -04BS-2 IO	↓ -0040	↓ -04B-2 IO	↓ -6044	↓ -04APBS-2 IO	4	
39-30-9027	5566-02BGS2-2 IO	39-31-0028	5566-02BGS-2 IO	39-31-0022	5566-02BS-2 IO	39-31-0020	5566-02B-2 IO	39-30-6024	5566-02APBS-2 IO	2	
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	CKT. SIZE	
5566-NBGS2-2 IO		5566-NBGS-2 IO		5566-NBS-2 IO		5566-NB-2 IO		5566-NAPBS-2 IO			
39-30-9246	5566-24BGS2	39-31-0247	5566-24BGS	39-31-0241	5566-24BS	39-29-3246	5566-24B	39-30-6243	5566-24APBS	24	
↑ -9226	↑ -22BGS2	↑ -0227	↑ -22BGS	↑ -0221	↑ -22BS	↑ -3226	↑ -22B	↑ -6223	↑ -22APBS	22	
-9206	-20BGS2	-0207	-20BGS	-0201	-20BS	-3206	-20B	-6203	-20APBS	20	
-9186	-18BGS2	-0187	-18BGS	-0181	-18BS	-3186	-18B	-6183	-18APBS	18	
-9166	-16BGS2	-0164	-16BGS	-0161	-16BS	-3166	-16B	-6163	-16APBS	16	
-9146	-14BGS2	-0147	-14BGS	-0141	-14BS	-3146	-14B	-6143	-14APBS	14	
-9126	-12BGS2	-0127	-12BGS	-0121	-12BS	-3126	-12B	-6123	-12APBS	12	
-9106	-10BGS2	-0107	-10BGS	-0101	-10BS	-3106	-10B	-6103	-10APBS	10	
-9086	-08BGS2	-0087	-08BGS	-0081	-08BS	-3086	-08B	-6083	-08APBS	8	
-9066	-06BGS2	-0067	-06BGS	-0061	-06BS	-3066	-06B	-6063	-06APBS	6	
↓ -9046	↓ -04BGS2	↓ -0047	↓ -04BGS	↓ -0041	↓ -04BS	↓ -3046	↓ -04B	↓ -6043	↓ -04APBS	4	
39-30-9026	5566-02BGS2	39-31-0027	5566-02BGS	39-31-0021	5566-02BS	39-29-3026	5566-02B	39-30-6023	5566-02APBS	2	
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	CKT. SIZE	
5566-NBGS2		5566-NBGS		5566-NBS		5566-NB		5566-NAPBS			

REVISED	EC NO: J2005-3557	2005/06/06	DRWN:WABEI	2005/06/07	CHKD:K1010	APPR:NUK1TA	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS		THIRD ANGLE PROJECTION	
										MM ONLY		---	METRIC			
								10 UNDER		± ---	DRAWN BY DATE		TITLE			
								10 OVER 30 UNDER		± ---	CHECKED BY DATE					
								30 OVER		± ---	APPROVED BY DATE					
K	REV	ANGULAR		± --- °	MATERIAL NO.		DOCUMENT NO.		SHEET NO.							
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-5566-002		3 OF 5								
		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION												



tb_frame_A3_J_ME_S

Rev. D 2004/04/02


9	8	7	6	5	4	3	2	EN-02JA(021)
---	---	---	---	---	---	---	---	--------------

	10	9	8	7	6	5	4	3	2	1																														
F							NOT	TOOLED	5566-24BPBS-3 IO	NOT	TOOLED	5566-24BPB-3 IO	24	F																										
								▲	-22BPBS-3 IO		▲	-22BPB-3 IO	22																											
									-20BPBS-3 IO			-20BPB-3 IO	20																											
									-18BPBS-3 IO			-18BPB-3 IO	18																											
									-16BPBS-3 IO			-16BPB-3 IO	16																											
									-14BPBS-3 IO			-14BPB-3 IO	14																											
									-12BPBS-3 IO			-12BPB-3 IO	12																											
									-10BPBS-3 IO			-10BPB-3 IO	10																											
									-08BPBS-3 IO			-08BPB-3 IO	8																											
									-06BPBS-3 IO			-06BPB-3 IO	6																											
E							▼		-04BPBS-3 IO	▼		-04BPB-3 IO	4	E																										
							NOT	TOOLED	5566-02BPBS-3 IO	NOT	TOOLED	5566-02BPB-3 IO	2																											
							EDP NO.		ENG. NO	EDP NO.		ENG. NO	CKT. SIZE																											
							5566-NBPBS-3 IO			5566-NBPB-3 IO																														
							39-31-0246		5566-24BPBS-2 IO	39-31-0244		5566-24BPB-2 IO	24																											
							▲	-0226	▲	-22BPBS-2 IO	▲	-0224	▲		-22BPB-2 IO	22																								
								-0206		-20BPBS-2 IO		-0204			-20BPB-2 IO	20																								
								-0186		-18BPBS-2 IO		-0184			-18BPB-2 IO	18																								
								-0166		-16BPBS-2 IO		-0164			-16BPB-2 IO	16																								
								-0146		-14BPBS-2 IO		-0144			-14BPB-2 IO	14																								
D								-0126		-12BPBS-2 IO		-0124		-12BPB-2 IO	12	D																								
								-0106		-10BPBS-2 IO		-0104		-10BPB-2 IO	10																									
								-0086		-08BPBS-2 IO		-0084		-08BPB-2 IO	8																									
								-0066		-06BPBS-2 IO		-0064		-06BPB-2 IO	6																									
							▼	-0046	▼	-04BPBS-2 IO	▼	-0044	▼	-04BPB-2 IO	4																									
							39-31-0026		5566-02BPBS-2 IO	39-31-0024		5566-02BPB-2 IO	2	CKT. SIZE																										
							EDP NO.		ENG. NO	EDP NO.		ENG. NO																												
							5566-NBPBS-2 IO			5566-NBPB-2 IO																														
							39-35-0248		5566-24A-400	39-31-0245		5566-24BPBS	39-31-0243	5566-24BPB	24		C																							
							▲	-0228	▲	-22A-400	▲	-0225	▲	-22BPBS	▲			-0223	▲	-22BPB	22																			
	-0208		-20A-400		-0205		-20BPBS		-0203		-20BPB	20																												
	-0188		-18A-400		-0185		-18BPBS		-0183		-18BPB	18																												
	-0168		-16A-400		-0165		-16BPBS		-0163		-16BPB	16																												
	-0148		-14A-400		-0145		-14BPBS		-0143		-14BPB	14																												
	-0128		-12A-400		-0125		-12BPBS		-0123		-12BPB	12																												
	-0108		-10A-400		-0105		-10BPBS		-0103		-10BPB	10																												
	-0088		-08A-400		-0085		-08BPBS		-0083		-08BPB	8																												
	-0068		-06A-400		-0065		-06BPBS		-0063		-06BPB	6																												
B							▼	-0048	▼	-04A-400	▼	-0045	▼	-04BPBS	▼	-0043	▼	-04BPB	4	B																				
							39-35-0028		5566-02A-400	39-31-0025		5566-02BPBS	39-31-0023	5566-02BPB	2																									
							EDP NO.		ENG. NO	EDP NO.		ENG. NO	EDP NO.		ENG. NO	CKT. SIZE																								
5566-NA-400			5566-NBPBS			5566-NBPB																																		
A							REVISED EC NO: J2005-3557 DRWN: MABEI CHKD: KTOJO APPR: NUKITA	2005/06/06 2005/06/07 2005/06/10	DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		NEW MINI FIT CONNECTOR HEADER HOUSING ASS'Y -LEAD FREE- MOLEX INCORPORATED SD-5566-002 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	SHEET NO. 4 OF 5	A																				
										10 UNDER	± ---	DRAWN BY H. HIRAMOTO	DATE '89/04/03	TITLE																										
										10 OVER 30 UNDER	± ---	CHECKED BY M. FUKUSHIMA	DATE '94/04/20																											
										30 OVER	± ---	APPROVED BY M. FUKUSHIMA	DATE '94/04/20	DOCUMENT NO.																										
										ANGULAR	± --- °	MATERIAL NO.																												
										DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-5566-002																										
												SIZE A3																												
1b_frame_A3_J_ME_S Rev. D 2004/04/02		9	8	7	6	5	4	3	2	EN-02JA(021)																														

[illegible]



極数別レイアウト図
(SCALE 1:1)



4	3	2	EN 031A/03
---	---	---	------------

tb_frame_A3_J_ME_S
Rev. D 2004/04/02

	10	9	8	7	6	5	4	3	2	1		
F									39-35-0248	5566-24A-400	24	F
									▲-0228	▲-22A-400	22	
									-0208	-20A-400	20	
									-0188	-18A-400	18	
									-0168	-16A-400	16	
									-0148	-14A-400	14	
									-0128	-12A-400	12	
									-0108	-10A-400	10	
									-0088	-08A-400	8	
									-0068	-06A-400	6	
E									▼-0048	▼-04A-400	4	E
									39-35-0028	5566-02A-400	2	
									EDP NO.	ENG. NO	極数	
									5566-NA-400			
	39-29-5247	5566-24APB-210	39-29-6248	5566-24AGS-210	39-28-8240	5566-24A-210	24					
	▲-5227	▲-22APB-210	▲-6228	▲-22AGS-210	▲-8220	▲-22A-210	22					
	-5207	-20APB-210	-6208	-20AGS-210	-8200	-20A-210	20					
	-5187	-18APB-210	-6188	-18AGS-210	-8180	-18A-210	18					
	-5167	-16APB-210	-6168	-16AGS-210	-8160	-16A-210	16					
	-5147	-14APB-210	-6148	-14AGS-210	-8140	-14A-210	14					
D	-5127	-12APB-210	-6128	-12AGS-210	-8120	-12A-210	12			D		
	-5107	-10APB-210	-6108	-10AGS-210	-8100	-10A-210	10					
	-5087	-08APB-210	-6088	-08AGS-210	-8080	-08A-210	8					
	-5067	-06APB-210	-6068	-06AGS-210	-8060	-06A-210	6					
	▼-5047	▼-04APB-210	▼-6048	▼-04AGS-210	▼-8040	▼-04A-210	4					
	39-29-5027	5566-02APB-210	39-29-6028	5566-02AGS-210	39-28-8020	5566-02A-210	2					
	EDP NO.	ENG. NO	EDP NO.	ENG. NO	EDP NO.	ENG. NO	極数					
	5566-NAPB-210		5566-NAGS-210		5566-NA-210							
	39-29-5246	5566-24APB	39-29-0243	5566-24AGS	39-28-1243	5566-24A	24					
	C	▲-5226	▲-22APB	▲-0223	▲-22AGS	▲-1223	▲-22A	22			C	
-5206		-20APB	-0203	-20AGS	-1203	-20A	20					
-5186		-18APB	-0183	-18AGS	-1183	-18A	18					
-5166		-16APB	-0163	-16AGS	-1163	-16A	16					
-5146		-14APB	-0143	-14AGS	-1143	-14A	14					
-5126		-12APB	-0123	-12AGS	-1123	-12A	12					
-5106		-10APB	-0103	-10AGS	-1103	-10A	10					
-5086		-08APB	-0083	-08AGS	-1083	-08A	8					
-5066		-06APB	-0063	-06AGS	-1063	-06A	6					
▼-5046		▼-04APB	▼-0043	▼-04AGS	▼-1043	▼-04A	4					
B	39-29-5026	5566-02APB	39-29-0023	5566-02AGS	39-28-1023	5566-02A	2			B		
	EDP NO.	ENG. NO	EDP NO.	ENG. NO	EDP NO.	ENG. NO	極数					
	5566-NAPB		5566-NAGS		5566-NA							
	REVISED EC NO: J2006-2418 DRWN: NABEI CHKD: KTOYODA APPR: NUKITA	DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
			10 UNDER	± ---	DRAWN BY H. HIRAMOTO	DATE '89/05/07	TITLE NEW MINI FIT CONNECTOR HEADER ASS'Y -LEAD FREE-					
			10 OVER 30 UNDER	± ---	CHECKED BY M. FUKUSHIMA	DATE '91/10/29						
			30 OVER	± ---	APPROVED BY M. ENOMOTO	DATE '91/10/29	MOLEX INCORPORATED					
			ANGULAR	± --- °	MATERIAL NO.		DOCUMENT NO.		SHEET NO.			
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-5566-003		2 OF 3			
					SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					
A	tb_frame_A3_J_ME_S Rev. D 2004/04/02	9	8	7	6	5	4	3	2	EN-02JA(021)		

	10	9	8	7	6	5	4	3	2	1																																																																																																																																																												
F												F																																																																																																																																																										
E												E																																																																																																																																																										
D	<table><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>24</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>22</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>20</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>18</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>39-33-3169</td><td>5566-16A-210-BU</td><td>39-33-3168</td><td>5566-16A-210-BL</td><td>16</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>14</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>12</td></tr><tr><td></td><td></td><td></td><td>39-33-4100</td><td>5566-10A-210-RE</td><td>39-33-3109</td><td>5566-10A-210-BU</td><td>39-33-3108</td><td>5566-10A-210-BL</td><td></td><td>10</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>39-33-3088</td><td>5566-08A-210-BL</td><td></td><td>8</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>6</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>4</td></tr><tr><td></td><td>39-34-5023</td><td>5566-02A-210-YE</td><td>39-33-4040</td><td>5566-04A-210-RE</td><td>39-33-3049</td><td>5566-04A-210-BU</td><td></td><td></td><td></td><td>2</td></tr><tr><td></td><td>EDP. NO.</td><td>ENG. NO.</td><td>EDP. NO.</td><td>ENG. NO.</td><td>EDP. NO.</td><td>ENG. NO.</td><td>EDP. NO.</td><td>ENG. NO.</td><td></td><td>極数</td></tr><tr><td></td><td colspan="2">5566-NA-210-YE</td><td colspan="2">5566-NA-210-RE</td><td colspan="2">5566-NA-210-BU</td><td colspan="2">5566-NA-210-BL</td><td></td><td></td></tr></table>																					24											22											20											18							39-33-3169	5566-16A-210-BU	39-33-3168	5566-16A-210-BL	16											14											12				39-33-4100	5566-10A-210-RE	39-33-3109	5566-10A-210-BU	39-33-3108	5566-10A-210-BL		10								39-33-3088	5566-08A-210-BL		8											6											4		39-34-5023	5566-02A-210-YE	39-33-4040	5566-04A-210-RE	39-33-3049	5566-04A-210-BU				2		EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.		極数		5566-NA-210-YE		5566-NA-210-RE		5566-NA-210-BU		5566-NA-210-BL				D
										24																																																																																																																																																												
										22																																																																																																																																																												
										20																																																																																																																																																												
										18																																																																																																																																																												
						39-33-3169	5566-16A-210-BU	39-33-3168	5566-16A-210-BL	16																																																																																																																																																												
										14																																																																																																																																																												
										12																																																																																																																																																												
			39-33-4100	5566-10A-210-RE	39-33-3109	5566-10A-210-BU	39-33-3108	5566-10A-210-BL		10																																																																																																																																																												
							39-33-3088	5566-08A-210-BL		8																																																																																																																																																												
										6																																																																																																																																																												
										4																																																																																																																																																												
	39-34-5023	5566-02A-210-YE	39-33-4040	5566-04A-210-RE	39-33-3049	5566-04A-210-BU				2																																																																																																																																																												
	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.		極数																																																																																																																																																												
	5566-NA-210-YE		5566-NA-210-RE		5566-NA-210-BU		5566-NA-210-BL																																																																																																																																																															
C	<table><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>24</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>22</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>20</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>18</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>16</td></tr><tr><td>39-33-3145</td><td>5566-14A-GR</td><td></td><td></td><td>39-33-3166</td><td>5566-16A-RE</td><td>39-33-3164</td><td>5566-16A-BU</td><td></td><td></td><td>14</td></tr><tr><td></td><td></td><td></td><td></td><td>39-33-3126</td><td>5566-12A-RE</td><td>39-33-3124</td><td>5566-12A-BU</td><td>39-33-3143</td><td>5566-14A-BL</td><td>12</td></tr><tr><td></td><td></td><td></td><td></td><td>39-33-3106</td><td>5566-10A-RE</td><td>39-33-3104</td><td>5566-10A-BU</td><td></td><td></td><td>10</td></tr><tr><td></td><td></td><td>39-33-3087</td><td>5566-08A-YE</td><td>39-33-3086</td><td>5566-08A-RE</td><td>39-33-3084</td><td>5566-08A-BU</td><td></td><td></td><td>8</td></tr><tr><td></td><td></td><td>39-33-3067</td><td>5566-06A-YE</td><td>39-33-3066</td><td>5566-06A-RE</td><td>39-33-3064</td><td>5566-06A-BU</td><td></td><td></td><td>6</td></tr><tr><td></td><td></td><td></td><td></td><td>39-33-3046</td><td>5566-04A-RE</td><td>39-33-3044</td><td>5566-04A-BU</td><td>39-33-3043</td><td>5566-04A-BL</td><td>4</td></tr><tr><td></td><td></td><td></td><td></td><td>39-33-3026</td><td>5566-02A-RE</td><td>39-33-3024</td><td>5566-02A-BU</td><td>39-33-3023</td><td>5566-02A-BL</td><td>2</td></tr><tr><td></td><td>EDP. NO.</td><td>ENG. NO.</td><td>EDP. NO.</td><td>ENG. NO.</td><td>EDP. NO.</td><td>ENG. NO.</td><td>EDP. NO.</td><td>ENG. NO.</td><td></td><td>極数</td></tr><tr><td></td><td colspan="2">5566-NA-GR</td><td colspan="2">5566-NA-YE</td><td colspan="2">5566-NA-RE</td><td colspan="2">5566-NA-BU</td><td colspan="2">5566-NA-BL</td></tr></table>																					24											22											20											18											16	39-33-3145	5566-14A-GR			39-33-3166	5566-16A-RE	39-33-3164	5566-16A-BU			14					39-33-3126	5566-12A-RE	39-33-3124	5566-12A-BU	39-33-3143	5566-14A-BL	12					39-33-3106	5566-10A-RE	39-33-3104	5566-10A-BU			10			39-33-3087	5566-08A-YE	39-33-3086	5566-08A-RE	39-33-3084	5566-08A-BU			8			39-33-3067	5566-06A-YE	39-33-3066	5566-06A-RE	39-33-3064	5566-06A-BU			6					39-33-3046	5566-04A-RE	39-33-3044	5566-04A-BU	39-33-3043	5566-04A-BL	4					39-33-3026	5566-02A-RE	39-33-3024	5566-02A-BU	39-33-3023	5566-02A-BL	2		EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.		極数		5566-NA-GR		5566-NA-YE		5566-NA-RE		5566-NA-BU		5566-NA-BL		C
										24																																																																																																																																																												
										22																																																																																																																																																												
										20																																																																																																																																																												
										18																																																																																																																																																												
										16																																																																																																																																																												
39-33-3145	5566-14A-GR			39-33-3166	5566-16A-RE	39-33-3164	5566-16A-BU			14																																																																																																																																																												
				39-33-3126	5566-12A-RE	39-33-3124	5566-12A-BU	39-33-3143	5566-14A-BL	12																																																																																																																																																												
				39-33-3106	5566-10A-RE	39-33-3104	5566-10A-BU			10																																																																																																																																																												
		39-33-3087	5566-08A-YE	39-33-3086	5566-08A-RE	39-33-3084	5566-08A-BU			8																																																																																																																																																												
		39-33-3067	5566-06A-YE	39-33-3066	5566-06A-RE	39-33-3064	5566-06A-BU			6																																																																																																																																																												
				39-33-3046	5566-04A-RE	39-33-3044	5566-04A-BU	39-33-3043	5566-04A-BL	4																																																																																																																																																												
				39-33-3026	5566-02A-RE	39-33-3024	5566-02A-BU	39-33-3023	5566-02A-BL	2																																																																																																																																																												
	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.	EDP. NO.	ENG. NO.		極数																																																																																																																																																												
	5566-NA-GR		5566-NA-YE		5566-NA-RE		5566-NA-BU		5566-NA-BL																																																																																																																																																													
B												B																																																																																																																																																										
A	<table><tr><td rowspan="5">REVISED EC NO: J2006-2418 DRAWN: NABEI CHKD: K10Y00A APPR: NUKITA</td><td rowspan="5">2006/01/30 2006/02/03 2006/02/06</td><td rowspan="5">DESCRIPTION REV</td><td colspan="2">GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td colspan="2">DIMENSION STYLE MM ONLY</td><td>SCALE ---</td><td>DESIGN UNITS METRIC</td><td rowspan="5"> THIRD ANGLE PROJECTION</td></tr><tr><td>10 UNDER</td><td>± ---</td><td>DRAWN BY H. HIRAMOTO</td><td>DATE '89/05/07</td><td colspan="2" rowspan="2">NEW MINI FIT CONNECTOR HEADER ASS'Y -LEAD FREE-</td></tr><tr><td>10 OVER 30 UNDER</td><td>± ---</td><td>CHECKED BY M. FUKUSHIMA</td><td>DATE '91/10/29</td></tr><tr><td>30 OVER</td><td>± ---</td><td>APPROVED BY M. ENOMOTO</td><td>DATE '91/10/29</td><td colspan="2" rowspan="2">MOLEX INCORPORATED</td></tr><tr><td colspan="2">ANGULAR ± --- °</td><td colspan="2">MATERIAL NO.</td><td>DOCUMENT NO.</td><td>SHEET NO.</td></tr><tr><td colspan="2">DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td colspan="2">SEE CHART</td><td colspan="2">SD-5566-003</td><td colspan="2">3 OF 3</td></tr><tr><td colspan="2">SIZE A3</td><td colspan="8">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td></tr></table>											REVISED EC NO: J2006-2418 DRAWN: NABEI CHKD: K10Y00A APPR: NUKITA	2006/01/30 2006/02/03 2006/02/06	DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	10 UNDER	± ---	DRAWN BY H. HIRAMOTO	DATE '89/05/07	NEW MINI FIT CONNECTOR HEADER ASS'Y -LEAD FREE-		10 OVER 30 UNDER	± ---	CHECKED BY M. FUKUSHIMA	DATE '91/10/29	30 OVER	± ---	APPROVED BY M. ENOMOTO	DATE '91/10/29	MOLEX INCORPORATED		ANGULAR ± --- °		MATERIAL NO.		DOCUMENT NO.	SHEET NO.	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-5566-003		3 OF 3		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								A																																																																																																								
REVISED EC NO: J2006-2418 DRAWN: NABEI CHKD: K10Y00A APPR: NUKITA	2006/01/30 2006/02/03 2006/02/06	DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION																																																																																																																																																													
			10 UNDER	± ---	DRAWN BY H. HIRAMOTO	DATE '89/05/07	NEW MINI FIT CONNECTOR HEADER ASS'Y -LEAD FREE-																																																																																																																																																															
			10 OVER 30 UNDER	± ---	CHECKED BY M. FUKUSHIMA	DATE '91/10/29																																																																																																																																																																
			30 OVER	± ---	APPROVED BY M. ENOMOTO	DATE '91/10/29	MOLEX INCORPORATED																																																																																																																																																															
			ANGULAR ± --- °		MATERIAL NO.					DOCUMENT NO.	SHEET NO.																																																																																																																																																											
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-5566-003		3 OF 3																																																																																																																																																																
SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																																																																																				
tb_frame_A3_J_ME_S Rev. D 2004/04/02	9	8	7	6	5	4	3	2	EN-02JA(021)																																																																																																																																																													

DWG. NO. SD-5566-N****-*	NOT TOOLED	5566-24APB-310	NOT TOOLED	5566-24AGS2-310	NOT TOOLED	5566-24AGS-310	NOT TOOLED	5566-22AS-310	NOT TOOLED	5566-22A-310	24
	▲	▲ -22APB-310	▲	▲ -22AGS2-310		▲ -22AGS-310	▲	▲ -22AS-310	▲	▲ -22A-310	22
		-20APB-310		-20AGS2-310		-20AGS-310		-20AS-310		-20A-310	20
		-18APB-310		-18AGS2-310		-18AGS-310		-18AS-310		-18A-310	18
		-16APB-310		-16AGS2-310		-16AGS-310		-16AS-310		-16A-310	16
		-14APB-310		-14AGS2-310		-14AGS-310		-14AS-310		-14A-310	14
		-12APB-310		-12AGS2-310		-12AGS-310		-12AS-310		-12A-310	12
		-10APB-310		-10AGS2-310		-10AGS-310		-10AS-310		-10A-310	10
		-08APB-310		-08AGS2-310		-08AGS-310		-08AS-310		-08A-310	8
		-06APB-310		-06AGS2-310		-06AGS-310		-06AS-310		-06A-310	6

NOT TOOLED	5566-02APB-310	NOT TOOLED	5566-02AGS2-310	NOT TOOLED	5566-02AGS-310	NOT TOOLED	5566-02AS-310	NOT TOOLED	5566-02A-310	2
------------	----------------	------------	-----------------	------------	----------------	------------	---------------	------------	--------------	---

EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	
---------	----------	---------	----------	---------	----------	---------	----------	---------	----------	--

5566-NAPB-310	5566-NAGS2-310	5566-NAGS-310	5566-NAS-310	5566-NA-310	CKT. SIZE
---------------	----------------	---------------	--------------	-------------	-----------

39-29-5247	5566-24APB-210	39-30-9245	5566-24AGS2-210	39-30-6242	5566-24AS-210	39-28-8240	5566-24A-210	24
------------	----------------	------------	-----------------	------------	---------------	------------	--------------	----

▲	▲ -5227	▲ -5225	▲ -5228	▲ -5222	▲ -5225	▲ -5220	▲ -5220	22
---	---------	---------	---------	---------	---------	---------	---------	----

-5207	-20APB-210	-9205	-20AGS2-210	-6202	-20AGS-210	-6202	-20AS-210	20
-------	------------	-------	-------------	-------	------------	-------	-----------	----

-5187	-18APB-210	-9185	-18AGS2-210	-6182	-18AGS-210	-6182	-18AS-210	18
-------	------------	-------	-------------	-------	------------	-------	-----------	----

-5167	-16APB-210	-9165	-16AGS2-210	-6162	-16AGS-210	-6162	-16AS-210	16
-------	------------	-------	-------------	-------	------------	-------	-----------	----

-5147	-14APB-210	-9145	-14AGS2-210	-6142	-14AGS-210	-6142	-14AS-210	14
-------	------------	-------	-------------	-------	------------	-------	-----------	----

-5127	-12APB-210	-9125	-12AGS2-210	-6122	-12AGS-210	-6122	-12AS-210	12
-------	------------	-------	-------------	-------	------------	-------	-----------	----

-5107	-10APB-210	-9105	-10AGS2-210	-6102	-10AGS-210	-6102	-10AS-210	10
-------	------------	-------	-------------	-------	------------	-------	-----------	----

-5087	-08APB-210	-9085	-08AGS2-210	-6082	-08AGS-210	-6082	-08AS-210	8
-------	------------	-------	-------------	-------	------------	-------	-----------	---

-5067	-06APB-210	-9065	-06AGS2-210	-6062	-06AGS-210	-6062	-06AS-210	6
-------	------------	-------	-------------	-------	------------	-------	-----------	---

39-29-5027	5566-02APB-210	39-30-9025	5566-02AGS2-210	39-30-6022	5566-02AS-210	39-28-8020	5566-02A-210	2
------------	----------------	------------	-----------------	------------	---------------	------------	--------------	---

EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	
---------	----------	---------	----------	---------	----------	---------	----------	--

5566-NAPB-210	5566-NAGS2-210	5566-NAGS-210	5566-NAS-210	5566-NA-210	CKT. SIZE
---------------	----------------	---------------	--------------	-------------	-----------

39-29-5246	5566-24APB	39-30-9244	5566-24AGS2	39-30-6241	5566-24AS	39-28-1243	5566-24A	24
------------	------------	------------	-------------	------------	-----------	------------	----------	----

▲	▲ -5226	▲ -9224	▲ -22AGS2	▲ -6221	▲ -22AS	▲ -1223	▲ -22A	22
---	---------	---------	-----------	---------	---------	---------	--------	----

-5206	-20APB	-9204	-20AGS2	-6201	-20AGS	-1203	-20A	20
-------	--------	-------	---------	-------	--------	-------	------	----

-5186	-18APB	-9184	-18AGS2	-6181	-18AGS	-1183	-18A	18
-------	--------	-------	---------	-------	--------	-------	------	----

-5166	-16APB	-9164	-16AGS2	-6161	-16AGS	-1163	-16A	16
-------	--------	-------	---------	-------	--------	-------	------	----

-5146	-14APB	-9144	-14AGS2	-6141	-14AGS	-1143	-14A	14
-------	--------	-------	---------	-------	--------	-------	------	----

-5126	-12APB	-9124	-12AGS2	-6121	-12AGS	-1123	-12A	12
-------	--------	-------	---------	-------	--------	-------	------	----

-5106	-10APB	-9104	-10AGS2	-6101	-10AGS	-1103	-10A	10
-------	--------	-------	---------	-------	--------	-------	------	----

-5086	-08APB	-9084	-08AGS2	-6081	-08AGS	-1083	-08A	8
-------	--------	-------	---------	-------	--------	-------	------	---

-5066	-06APB	-9064	-06AGS2	-6061	-06AGS	-1063	-06A	6
-------	--------	-------	---------	-------	--------	-------	------	---

39-29-5026	5566-02APB	39-30-9024	5566-02AGS2	39-30-6021	5566-02AS	39-28-1023	5566-02A	2
------------	------------	------------	-------------	------------	-----------	------------	----------	---

EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	
---------	----------	---------	----------	---------	----------	---------	----------	--

5566-NAPB	5566-NAGS2	5566-NAGS	5566-NAS	5566-NA	CKT. SIZE
-----------	------------	-----------	----------	---------	-----------

5566-N****-*		SEE NOTE 2		REVISE ONLY ON CAD SYSTEM		TITLE 名称 NEW MINI FIT CONNECTOR HEADER HOUSING ASS'Y -LEAD FREE-		DWG. NO. SHEET 2 OF 4 SD-5566-N****-*		REV J	
MODEL NO.		SEE SHEET 1 OF 4		SEE SHEET 1 OF 4		SEE NOTE 2		DRAWN BY 99/4/3 H.HIRAMOTO		CHK'D BY 99/4/20 M.FUKUSHIMA	
角 度 ANGLE		3°		90°		90°		90°		90°	
30°		10.3		10.3		10.3		10.3		10.3	
10°		3.0		10.25		10.25		10.25		10.25	
10°		10.2		10.2		10.2		10.2		10.2	
GENERAL TOLERANCES		D		SEE SHEET 1 OF 4		SEE SHEET 1 OF 4		SEE SHEET 1 OF 4		SEE SHEET 1 OF 4	
LTR		REVISION RECORD		DR. CHK.		DATE		M.FUKUSHIMA		SCALE 1:1	

DWG. NO. SD-5566-N****-*									
NOT TOOLED	5566-24BGS2-310	NOT TOOLED	5566-24BGS-310	NOT TOOLED	5566-24BS-310	NOT TOOLED	5566-24B-310	NOT TOOLED	5566-24APBS-310
▲	▲ -22BGS2-310	▲	▲ -22BGS-310	▲	▲ -22BS-310	▲	▲ -22B-310	▲	▲ -22APBS-310
	-20BGS2-310		-20BGS-310		-20BS-310		-20B-310		-20APBS-310
	-18BGS2-310		-18BGS-310		-18BS-310		-18B-310		-18APBS-310
	-16BGS2-310		-16BGS-310		-16BS-310		-16B-310		-16APBS-310
	-14BGS2-310		-14BGS-310		-14BS-310		-14B-310		-14APBS-310
	-12BGS2-310		-12BGS-310		-12BS-310		-12B-310		-12APBS-310
	-10BGS2-310		-10BGS-310		-10BS-310		-10B-310		-10APBS-310
	-08BGS2-310		-08BGS-310		-08BS-310		-08B-310		-08APBS-310
	-06BGS2-310		-06BGS-310		-06BS-310		-06B-310		-06APBS-310
▼	▼ -04BGS2-310	▼	▼ -04BGS-310	▼	▼ -04BS-310	▼	▼ -04B-310	▼	▼ -04APBS-310
NOT TOOLED	5566-02BGS2-310	NOT TOOLED	5566-02BGS-310	NOT TOOLED	5566-02BS-310	NOT TOOLED	5566-02B-310	NOT TOOLED	5566-02APBS-310
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.

5566-NBGS2-310									
39-30-9247	5566-24BGS2-210	39-31-0248	5566-24BGS-210	39-31-0242	5566-24BS-210	39-31-0240	5566-24B-210	39-30-6244	5566-24APBS-210
▲	▲ -22BGS2-210	▲ -0228	▲ -22BGS-210	▲ -0222	▲ -22BS-210	▲ -0220	▲ -22B-210	▲ -6224	▲ -22APBS-210
-9207	-20BGS2-210	-0208	-20BGS-210	-0202	-20BS-210	-0200	-20B-210	-6204	-20APBS-210
-9187	-18BGS2-210	-0188	-18BGS-210	-0182	-18BS-210	-0180	-18B-210	-6184	-18APBS-210
-9167	-16BGS2-210	-0168	-16BGS-210	-0162	-16BS-210	-0160	-16B-210	-6164	-16APBS-210
-9147	-14BGS2-210	-0148	-14BGS-210	-0142	-14BS-210	-0140	-14B-210	-6144	-14APBS-210
-9127	-12BGS2-210	-0128	-12BGS-210	-0122	-12BS-210	-0120	-12B-210	-6124	-12APBS-210
-9107	-10BGS2-210	-0108	-10BGS-210	-0102	-10BS-210	-0100	-10B-210	-6104	-10APBS-210
-9087	-08BGS2-210	-0088	-08BGS-210	-0082	-08BS-210	-0080	-08B-210	-6084	-08APBS-210
-9067	-06BGS2-210	-0068	-06BGS-210	-0062	-06BS-210	-0060	-06B-210	-6064	-06APBS-210
▼ -9047	▼ -04BGS2-210	▼ -0048	▼ -04BGS-210	▼ -0042	▼ -04BS-210	▼ -0040	▼ -04B-210	▼ -6044	▼ -04APBS-210
39-30-9027	5566-02BGS2-210	39-31-0028	5566-02BGS-210	39-31-0022	5566-02BS-210	39-31-0020	5566-02B-210	39-30-6024	5566-02APBS-210
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.

5566-NBGS2-210									
39-30-9246	5566-24BGS2	39-31-0247	5566-24BGS	39-31-0241	5566-24BS	39-29-3246	5566-24B	39-30-6243	5566-24APBS
▲	▲ -22BGS2	▲ -0227	▲ -22BGS	▲ -0221	▲ -22BS	▲ -3226	▲ -22B	▲ -6223	▲ -22APBS
-9206	-20BGS2	-0207	-20BGS	-0201	-20BS	-3206	-20B	-6203	-20APBS
-9186	-18BGS2	-0187	-18BGS	-0181	-18BS	-3186	-18B	-6183	-18APBS
-9166	-16BGS2	-0164	-16BGS	-0161	-16BS	-3166	-16B	-6163	-16APBS
-9146	-14BGS2	-0147	-14BGS	-0141	-14BS	-3146	-14B	-6143	-14APBS
-9126	-12BGS2	-0127	-12BGS	-0121	-12BS	-3126	-12B	-6123	-12APBS
-9106	-10BGS2	-0107	-10BGS	-0101	-10BS	-3106	-10B	-6103	-10APBS
-9086	-08BGS2	-0087	-08BGS	-0081	-08BS	-3086	-08B	-6083	-08APBS
-9066	-06BGS2	-0067	-06BGS	-0061	-06BS	-3066	-06B	-6063	-06APBS
▼ -9046	▼ -04BGS2	▼ -0047	▼ -04BGS	▼ -0041	▼ -04BS	▼ -3046	▼ -04B	▼ -6043	▼ -04APBS
39-30-9026	5566-02BGS2	39-31-0027	5566-02BGS	39-31-0021	5566-02BS	39-29-3026	5566-02B	39-30-6023	5566-02APBS
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.

A									
:MM DIMENSIONS IN M									

NOT	TOOLED	5566-24BPBS-310	NOT	TOOLED	5566-24BPB-310	24
	▲	-22BPBS-310		▲	-22BPB-310	22
		-20BPBS-310			-20BPB-310	20
		-18BPBS-310			-18BPB-310	18
		-16BPBS-310			-16BPB-310	16
		-14BPBS-310			-14BPB-310	14
		-12BPBS-310			-12BPB-310	12
		-10BPBS-310			-10BPB-310	10
		-08BPBS-310			-08BPB-310	8
		-06BPBS-310			-06BPB-310	6
	▼	-04BPBS-310		▼	-04BPB-310	4
NOT	TOOLED	5566-02BPBS-310	NOT	TOOLED	5566-02BPB-310	2
EDP NO.	ENG. NO	EDP NO.	ENG. NO	EDP NO.	ENG. NO	CKT. SIZE
5566-NBPPS-310						
39-31-0246	5566-24BPBS-210	39-31-0244	5566-24BPB-210	24		
▲	-0226	▲	-0224	▲	-22BPB-210	22
	-0206		-0204		-20BPB-210	20
	-0186		-0184		-18BPB-210	18
	-0166		-0164		-16BPB-210	16
	-0146		-0144		-14BPB-210	14
	-0126		-0124		-12BPB-210	12
	-0106		-0104		-10BPB-210	10
	-0086		-0084		-08BPB-210	8
	-0066		-0064		-06BPB-210	6
▼	-0046	▼	-0044	▼	-04BPB-210	4
39-31-0026	5566-02BPBS-210	39-31-0024	5566-02BPB-210	2		
EDP NO.	ENG. NO	EDP NO.	ENG. NO			CKT. SIZE
5566-NBPBS-210						
39-31-0245	5566-24BPBS	39-31-0243	5566-24BPB	24		
▲	-0225	▲	-0223	▲	-22BPB	22
	-0205		-0203		-20BPB	20
	-0185		-0183		-18BPB	18
	-0165		-0163		-16BPB	16
	-0145		-0143		-14BPB	14
	-0125		-0123		-12BPB	12
	-0105		-0103		-10BPB	10
	-0085		-0083		-08BPB	8
	-0065		-0063		-06BPB	6
▼	-0045	▼	-0043	▼	-04BPB	4
39-31-0025	5566-02BPBS	39-31-0023	5566-02BPB	2		
EDP NO.	ENG. NO	EDP NO.	ENG. NO			CKT. SIZE
5566-NA-400						
39-35-0028	5566-24A-400					
▲	-22A-400					
	-20A-400					
	-18A-400					
	-16A-400					
	-14A-400					
	-12A-400					
	-10A-400					
	-08A-400					
	-06A-400					
▼	-04A-400					
39-35-0028	5566-02A-400					
EDP NO.	ENG. NO					

MOLEX-JAPAN CO.,LTD.

ニコレ、日本モリックス株式会社

SEE NOTE 2	REVISE ONLY ON CAD SYSTEM
	TITLE 名称

HEADER HOUSING ASS'Y

-LEAD FREE-

DWG. NO. SHEET 4 OF 4 RE

SD-5566-N***-***

E USED WITHOUT WRITTEN PERMISSION

1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100



5566-NA**-*
MODEL NO.

5566.S21

ENG. NO
SD-5566-NA***

EDP NO.
表 参照

MM DIMENSIONS IN METRIC DO NOT SCALE DRAWING

8

7

6

5

4

3

2

1

39-35-0248	5566-24A-400	24
▲-0228	▲-22A-400	22
-0208	-20A-400	20
-0188	-18A-400	18
-0168	-16A-400	16
-0148	-14A-400	14
-0128	-12A-400	12
-0108	-10A-400	10
-0088	-08A-400	8
-0068	-06A-400	6
▼-0048	▼-04A-400	4
39-35-0028	5566-02A-400	2
EDP NO.	ENG. NO	極数
5566-NA-400		

39-29-5247	5566-24APB-210	39-29-6248	5566-24AGS-210	39-28-8240	5566-24A-210	24
▲-5227	▲-22APB-210	▲-6228	▲-22AGS-210	▲-8220	▲-22A-210	22
-5207	-20APB-210	-6208	-20AGS-210	-8200	-20A-210	20
-5187	-18APB-210	-6188	-18AGS-210	-8180	-18A-210	18
-5167	-16APB-210	-6168	-16AGS-210	-8160	-16A-210	16
-5147	-14APB-210	-6148	-14AGS-210	-8140	-14A-210	14
-5127	-12APB-210	-6128	-12AGS-210	-8120	-12A-210	12
-5107	-10APB-210	-6108	-10AGS-210	-8100	-10A-210	10
-5087	-08APB-210	-6088	-08AGS-210	-8080	-08A-210	8
-5067	-06APB-210	-6068	-06AGS-210	-8060	-06A-210	6
▼-5047	▼-04APB-210	▼-6048	▼-04AGS-210	▼-8040	▼-04A-210	4
39-29-5027	5566-02APB-210	39-29-6028	5566-02AGS-210	39-28-8020	5566-02A-210	2
EDP NO.	ENG. NO	EDP NO.	ENG. NO	EDP NO.	ENG. NO	極数
5566-NAPB-210						

39-29-5246	5566-24APB	39-29-0243	5566-24AGS	39-28-1243	5566-24A	24
▲-5226	▲-22APB	▲-0223	▲-22AGS	▲-1223	▲-22A	22
-5206	-20APB	-0203	-20AGS	-1203	-20A	20
-5186	-18APB	-0183	-18AGS	-1183	-18A	18
-5166	-16APB	-0163	-16AGS	-1163	-16A	16
-5146	-14APB	-0143	-14AGS	-1143	-14A	14
-5126	-12APB	-0123	-12AGS	-1123	-12A	12
-5106	-10APB	-0103	-10AGS	-1103	-10A	10
-5086	-08APB	-0083	-08AGS	-1083	-08A	8
-5066	-06APB	-0063	-06AGS	-1063	-06A	6
▼-5046	▼-04APB	▼-0043	▼-04AGS	▼-1043	▼-04A	4
39-29-5026	5566-02APB	39-29-0023	5566-02AGS	39-28-1023	5566-02A	2
EDP NO.	ENG. NO	EDP NO.	ENG. NO	EDP NO.	ENG. NO	極数
5566-NAPB						

5566-NA***		5566-NAGS		5566-NA	
MODEL NO.		FINISH		EDP NO.	
角 度 ANGLE		仕 上 げ 注 記 2 参 照		表 参 照	
30°以上		適用電線範囲		ENG. NO.	
100%以上		被覆外径		SHEET 2 OF 2	
100%以上		INS. RANGE		SD-5566-NA***	
未注		90°/5/7		TITLE 名称	
100%以上		CHK'D BY 91/0/29		NEW MINI FIT CONNECTOR	
未注		日付 H.HIRAMOTO		HEADER ASS'Y -LEAD FREE-	
100%以上		APPD BY 91/0/29		SCALE	
100%以上		MEMO		1:1	
一般公差		REVISE ONLY ON CAD SYSTEM		1:1	
GENERAL TOLERANCES		MATERIAL		MOLEX-JAPAN CO.,LTD.	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX(JAPAN) AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
本図面は日本モリックス(株)の所有する情報を含むもので 当社の許可なく複製を禁止する。