



Up to 60% Off | 30-Day Money Back Guarantee | One-year Warranty
 Jameco's ValuePro products are brand name quality at significant price savings.
 1-800-831-4242 | www.Jameco.com

KM Series Standard 105°C

Features

- ◆ Used in communication equipments, switching power supply, etc.
- ◆ Safety vent construction design.
- ◆ For detail specifications, please refer to Engineering Bulletin No.E102

Specifications

Item	Performance Characteristics										
Operating Temperature Range	-40 to +105°C					-25 to +105°C					
Rated voltage Range	6.3 to 100 VDC					160 to 450 VDC					
Capacitance Range	0.1 to 15000μF					0.47 to 220μF					
Capacitance Tolerance	±20% (120Hz, +20°C)										
LeaKage Current (+20°C,max)	I≤0.01 CV or 3(μA) After 1 minute whichever is greater measured with rated working voltage applied. I≤0.03 CV.(μA) After 1 minute with rated working voltage applied.										
Dissipation Factor(tanδ)	Working Voltage(VDC)										
	6.3	10	16	25	35	50	63	100			
	D.F.(%)max.										
	24	20	16	14	12	10	9	9			
Dissipation Factor(tanδ)	Working Voltage(VDC)										
	160	200	250	350	400	450					
	D.F.(%)max.										
	15	15	15	15	15	18					
For capacitance > 1000 uF, add 2% per another 1000uF. (+20°C,at 120Hz)											
Low Temperature Characteristics (120 Hz)	Impedance ratio max.										
	Working Voltage(VDC)										
	6.3	10	16	25	35	50	63	100			
	Z-25°C/Z+20°C										
	4	3	2	2	2	2	2	2			
Low Temperature Characteristics (120 Hz)	Z-40°C/Z+20°C										
	8	6	4	3	3	3	3	3			
	Working Voltage(VDC)										
	160	200	250	350	400	450					
Low Temperature Characteristics (120 Hz)	Z-25°C/Z+20°C										
	2	2	3	5	6	15					
	For Capacitance Value 1000 uF,Add 0.5 per another 1000 uF for -25°C/+ 20°C Add 1 per another 1000 uF for -40°C/+20°C										
	Load Life	Test conditions									
Duration time : 2000 Hrs											
Ambient temperature:+105°C											
Applied voltage : Rated DC working voltage											
After test requirements at +20°C											
Capacitance change: ≤±20% of the initial measured value											
Load Life	Dissipation factor : ≤200% of the initial specified value										
	Leakage current : ≤ The initial specified value										
Shelf Life	Test conditions										
	Duration time : 500 Hrs										
	Ambient temperature:+105°C										
	Applied voltage : None										
	After test requirements at +20°C: Same limits as Load life.										
	Pre-treatment for measurements shall be conducted after application of DC working voltage for 30 minutes.										



Up to 60% Off | 30-Day Money Back Guarantee | One-year Warranty
 Jameco's ValuePro products are brand name quality at significant price savings.
 1-800-831-4242 | www.Jameco.com

Diagram of Dimensions:(Unit:mm)

D ϕ	5	6.3	8	10	13	16	18	22
F	2.0	2.5	3.5	5.0	5.0	7.5	7.5	10
d ϕ	0.5			0.6		0.8		

Case Size

WV(SV) uF	gDxL(mm)													
	6.3 (8)	10 (13)	16 (20)	25 (32)	35 (44)	50 (63)	63 (79)	100 (125)	160 (200)	200 (250)	250 (300)	350 (400)	400 (450)	450 (500)
0.1					→	5x11	5x11	5x11	-	-	-	-	-	-
0.22					→	5x11	5x11	5x11	-	-	-	-	-	-
0.33					→	5x11	5x11	5x11	-	-	-	-	-	-
0.47					→	5x11	5x11	5x11	5x11	5x11	5x11	6.3x11	6.3x11	6.3x11
1					→	5x11	5x11	5x11	6.3x11	6.3x11	6.3x11	6.3x11	8x11.5	8x11.5
2.2					→	5x11	5x11	5x11	6.3x11	6.3x11	8x11.5	10x12.5	10x12.5	10x16
3.3					→	5x11	5x11	5x11	6.3x11	8x11.5	8x11.5	10x16	10x16	10x20
4.7					→	5x11	5x11	5x11	8x11.5	8x11.5	10x12.5	10x16	10x16	10x20
10					→	5x11	6.3x11	6.3x11	10x16	10x16	10x20	10x20	13x20	13x25
22				→	5x11	6.3x11	6.3x11	8x11.5	10x20	10x20	13x20	13x25	16x25	16x31.5
33				→	5x11	6.3x11	8x11.5	10x12.5	10x20	13x20	13x25	16x25	16x31.5	16x35.5
47	→	5x11	5x11	6.3x11	6.3x11	6.3x11	8x11.5	10x16	13x25	13x25	13x25	16x31.5	16x35.5	-
100	5x11	6.3x11	6.3x11	6.3x11	8x11.5	10x12.5	10x16	13x20	16x25	16x25	16x31.5	-	-	-
220	6.3x11	6.3x11	8x11.5	10x12.5	10x12.5	10x16	10x20	16x25	16x35.5	-	-	-	-	-
330	8x11.5	8x11.5	8x11.5	10x12.5	10x16	10x20	13x20	16x31.5	-	-	-	-	-	-
470	8x11.5	8x11.5	10x12.5	10x16	10x20	13x20	13x25	16x31.5	-	-	-	-	-	-
1000	10x12.5	10x16	10x20	13x20	13x25	16x25	16x31.5	-	-	-	-	-	-	-
2200	10x20	13x20	13x25	16x25	16x31.5	18x35.5	-	-	-	-	-	-	-	-
3300	13x20	13x25	16x31.5	16x35.5	18x35.5	18x35.5	-	-	-	-	-	-	-	-
4700	13x25	16x25	16x31.5	16x35.5	18x41	-	-	-	-	-	-	-	-	-
6800	16x25	16x31.5	18x35.5	18x41	-	-	-	-	-	-	-	-	-	-
10000	16x31.5	18x35.5	18x41	-	-	-	-	-	-	-	-	-	-	-
15000	18x35.5	-	-	-	-	-	-	-	-	-	-	-	-	-



Up to 60% Off | 30-Day Money Back Guarantee | One-year Warranty
 Jameco's ValuePro products are brand name quality at significant price savings.
 1-800-831-4242 | www.Jameco.com

Maximum Ripple Current

		(mA,rms,120Hz at 105°C)												
WV(SV) uF	6.3 (8)	10 (13)	16 (20)	25 (32)	35 (44)	50 (63)	63 (79)	100 (125)	160 (200)	200 (250)	250 (300)	350 (400)	400 (450)	450 (500)
0.1	—	—	—	—	→	8	8	10	-	-	-	-	-	-
0.22	—	—	—	—	→	8	8	10	-	-	-	-	-	-
0.33	—	—	—	—	→	8	8	10	-	-	-	-	-	-
0.47	—	—	—	—	→	8	8	10	12	12	12	14	14	14
1	—	—	—	—	→	12	12	15	17	17	17	20	20	20
2.2	—	—	—	—	→	20	20	23	25	25	29	35	35	35
3.3	—	—	—	—	→	25	28	32	36	36	42	47	47	54
4.7	—	—	→	26	28	30	34	37	43	50	50	55	55	60
10	—	→	35	38	41	46	50	56	59	59	64	79	79	87
22	→	49	54	57	61	68	82	96	96	96	110	130	145	165
33	54	60	64	69	75	90	100	120	125	140	140	175	185	210
47	65	70	99	105	110	125	135	160	165	165	180	230	240	-
100	95	105	125	135	170	180	225	245	270	285	310	-	-	-
220	160	175	215	230	300	345	400	450	480	-	-	-	-	-
330	195	245	260	335	400	460	540	700	-	-	-	-	-	-
470	270	290	370	440	520	610	700	880	-	-	-	-	-	-
1000	460	550	640	770	920	1080	1210	-	-	-	-	-	-	-
2200	810	860	1000	1170	1340	1530	-	-	-	-	-	-	-	-
3300	960	1100	1300	1460	1650	1750	-	-	-	-	-	-	-	-
4700	1330	1400	1600	1780	1900	-	-	-	-	-	-	-	-	-
6800	1500	1690	1900	1950	-	-	-	-	-	-	-	-	-	-
10000	1765	1950	2060	-	-	-	-	-	-	-	-	-	-	-
15000	2075	-	-	-	-	-	-	-	-	-	-	-	-	-

Multiplier for ripple current vs. Frequency

CAP(uF) \ Hz		50(60)	120	400	1K	10K	50K-100K
Multiplier	CAP ≤ 10	0.8	1	1.30	1.30	1.65	1.70
	10 < CAP ≤ 100	0.8	1	1.23	1.23	1.48	1.53
	100 < CAP ≤ 1000	0.8	1	1.16	1.16	1.35	1.38
	1000 < CAP	0.8	1	1.11	1.11	1.25	1.28

Multiplier for Ripple Current vs. Temperature

Temperature	45	60	70	85	105
Multiplier	2.10	1.90	1.40	1.25	1.00