



CAUTION!
WEIGHT IS 87LBS

PROPERTY AND COPYRIGHT NOTICE
THIS DRAWING AND THE INFORMATION IT CONVEYS ARE THE PROPERTY OF HAMMOND MANUFACTURING. IT MAY NOT BE REPRODUCED,
TRANSMITTED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF HAMMOND MANUFACTURING.

REV.#	REVISION	DATE
0	RELEASED.	11/11/2019



DWG. BY: C. ILIE
APP'D. BY:
DATE: 11/11/2019
DIMENSIONS: IN(X) MM()

ELECTRICAL DATA:		
TESTS	CONDITIONS	ACCEPTANCE CRITERIA
lex	@ 5V, 60Hz, 50A DC	1.153 - 1.560A
Inductance	@ 50ADC =	10mH ± 15%
DCR	@ 20°C, LUG - LUG =	0.023 Ω ± 15%
	OPERATING VOLTAGE	750 VAC max.
	OPERATING VOLTAGE	600 VDC max.
	OPERATING TEMPERATURE	CLASS B 130°C
HIPOT	PRIMARY - CORE	2500V, 60Hz, 1 SEC
WEIGHT		87 LBS.

ELECTRONIC DIVISION
52 RANKIN PLACE,
WATERLOO, ONTARIO, N2J 3Z5 PH # (519) 886-6181
FAX # (519) 886-9540
TITLE: HIGH CURRENT
INDUCTOR
DWG. NO.
195J50